

Selection Guide / Accessories



Power Adapters >>				
Model Name	AS-120P-48	41-136040	41-136041	41-136042
Output				
DC Voltage	48VDC	12VDC	12VDC	12VDC
Current Range	0-2.5A	0-3A	0-3A	0-3A
Rated Power	120W	36W	36W	36W
Input				
90 - 264VDC	√	√	√	√
Machanical				
Casing	plastic	plastic	plastic	plastic
Installation*	-	-	-	-
Operating Temperature				
0°C to 55°C	√	-	-	-
-40°C to 75°C	-	√	√	√
Output Connector				
DC Jack with latch	√	-	√	-
Open Wire for Terminal Block	-	-	-	√
DC Plug	-	√	-	-



Power Adapters >>			
Model Name	41-136043	41-136044	41-136046
Output			
DC Voltage	12VDC	12VDC	12VDC
Current Range	0-3A	0-3A	0-3A
Rated Power	36W	36W	36W
Input			
90 - 264VDC	√	√	√
Machanical			
Casing	aluminum	aluminum	aluminum
Installation*	W	W	W
Operating Temperature			
0°C to 55°C	-	-	-
-40°C to 75°C	√	√	√
Output Connector			
DC Jack with latch	-	√	-
Open Wire for Terminal Block	-	-	√
DC Plug	√	-	-

* D: DIN-Rail Mounting, P: Panel Mounting, R: Rack Mounting, W: Wall Mounting

Ethernet Switches
Media Converters
Ethernet Extenders
Serial Device Servers
Accessories