

Selection Guide / Accessories



Nic Cards >>			
Model Name	GE3000-TX	GE3000-SX/LX	EN301
Ethernet Interface			
Max. 10/100 BASE-TX	-	-	1
Max. 100 BASE-FX	1	-	-
Max. 1000 BASE-SX/LX	-	1	-
Bus Interface			
PCI Express	√	√	-
PCI	-	-	√
Mode of Operations			
Auto-negotiation, Auto-MDI/MDI-X	√	√	√
Flow Control	√	√	√
Store & Forward	√	√	√
Machanical			
Dimensions (LxW)	125x121	125x121	133x117.5 / 133x80
Management Function			
ACPI*	√	√	√
Wake-on -LAN remote wake-up	√	-	-
IEEE802.1Q VLAN	√	√	√
IEEE802.1P Layer 2 Priority Tagging	√	√	√
NDIS5 Checksum Offload	√	√	√
RFC1157 SNMP v1	√	√	-
Preboot Execution Environment	√	√	-
Cable Diagnostic Utility	√	√	-
Jumbo Frame	√	√	-
Operating Temperature			
0°C to 45°C	√	√	√
Driver Supports			
Windows	Windows Vista, Windows 2003, Windows XP, Windows 2000, Windows ME, Windows 98SE		Windows XP, Windows 2000, Windows ME, Windows 98, Windows 95, Windows NT 3.51/4.0, Work Group 3.11
Novell	Netware 4.2 - 4.6	Netware 4.2 - 4.6	Netware 3.11, 3.12, 4.x, 5.x, 6.0 Clinet 32, Netware Client
Unix	Linux 2.4/2.6	Linux 2.4/2.6	RedHat Linux 6.2, 7.0, 7.1 UnixWare 8.0, SCO UNIX 5.0
Others	-	-	LAN Manager, LANtastic, PC-NFS, NCSA Telnet, FreeBSD 3.2, 4.0, 4.11, 4.2
Regulatory Approvals			
CE / FCC	Class B	Class B	Class B

* Advanced Configuration & Power Interface