

# EN400 シリーズ

PCI Express 100BASE-FX/SFP イーサネット アダプタ



## 特長

本商品につきましては2021年7月31日をもって販売を終了させて頂きました。代替製品については [こちらのページ](#) をご覧ください。

- » SFP slot and low-profile version availability
- » Supports PCI Express 1.1
- » Wake-on-LAN and remote wake-up support
- » Supports 1-Lane 2.5Gbps PCI Express Bus
- » 0 to 50°C operating temperature range

## 機能

- Compliant IEEE802.3 10BASE-T, 802.3u 100BASE-TX/FX/SFP
- Supports PCI Express 1.1
- Various Type of Cable Support - Twisted Pair Cable or Fiber Optic Cable
- Plug-and-Play Support
- Wake-on-LAN and remote wake-up support
- Full Duplex flow control (IEEE 802.3x)
- IEEE 802.1P Layer 2 Priority Encoding
- IEEE 802.1Q VLAN tagging
- Supports power down/link down power saving (for EN400TX)
- Supports 1-Lane 2.5Gbps PCI Express Bus
- 0 to 50°C operating temperature range

## 仕様

### Technology

#### Standards

- IEEE802.3
- IEEE802.3u

#### Protocols

- IEEE802.3x Full-duplex flow control Driver
  - Microsoft Windows 98, Windows ME, Windows XP, Windows 2000, Windows 2003, Windows Vista, Windows 7 and Windows 2008
  - SCO Unix 5.0.6 and 5.0.7
  - SCO OpenServer 6 and UnixWare 7.1.x.
  - FreeBSD 7.x and 8.0
  - Linux kernel 2.6.x and 2.4.x (Support x86 and x64)
  - Novell server driver (Support OS 6.x, 5.x), client for DOS (ODI driver)
  - MacOS 10.4 and 10.5 on Intel-based Mac computer, 10.6 on Intel-based Mac computer.
- 

### Power

#### Power Consumption

- 2W Max.
- 

### Mechanical

#### Dimensions:

\* Low Profile

- 80mm (W) x 119.2mm (D)  
(3.2"(W) x 4.76"(D))

\* Regular

- 117.5 mm (W) x 119.2 mm (D)  
(4.7"(W) x 4.76"(D))

#### Weight

- 80g (0.18lb.)
-

## Interface

### Ethernet Port

- 100BASE-FX: 1 port

### LED Indicators

- Per Unit: Link/Activity, SPD
- 

## Environment

### Operating Temperature

- 0°C to 50°C (32°F to 122°F)

### Storage Temperature

- -10°C to 70°C (14°F to 158°F)

### Ambient Relative Humidity

- 5% to 95% (non-condensing)
- 

## Regulatory Approvals


### ISO

- Manufactured in an ISO9001 facility

### EMI

- CE Mark Class B
  - FCC Part 15 Class B
  - VCCI Class B
-

## 寸法図



## 製品型番

### Model

|             |                                                                                            |
|-------------|--------------------------------------------------------------------------------------------|
| EN400C      | 100BASE-FX Multi Mode (SC) Ethernet Adapter                                                |
| EN400T      | 100BASE-FX Multi Mode (ST) Ethernet Adapter                                                |
| EN400C-20   | 100BASE-FX Single Mode (SC) -20Km Ethernet Adapter                                         |
| EN400C-40   | 100BASE-FX Single Mode (SC) -40Km Ethernet Adapter                                         |
| EN400T-20   | 100BASE-FX Single Mode (ST) -20Km Ethernet Adapter                                         |
| EN400CA-20  | 100BASE-FX Single Mode (SC) WDM-TX :1310nm/RX :1550nm -20Km Ethernet Adapter               |
| EN400CB-20  | 100BASE-FX Single Mode (SC) WDM-TX :1550nm/RX :1310nm -20Km Ethernet Adapter               |
| EN400CA-40  | 100BASE-FX Single Mode (SC) WDM-TX :1310nm/RX :1550nm -40Km Ethernet Adapter               |
| EN400CB-40  | 100BASE-FX Single Mode (SC) WDM-TX :1550nm/RX :1310nm -40Km Ethernet Adapter               |
| EN400LC     | 100BASE-FX Multi Mode (LC) -2Km Ethernet Adapter                                           |
| EN400PB     | 100BASE-SX (SC) 850nm Multi-Mode Fiber Fast Ethernet Adapter                               |
| EN400SFP    | 100BASE SFP Ethernet Adapter                                                               |
| EN400PC     | 100BASE-FX Multi Mode (SC) Ethernet Adapter (Low profile)                                  |
| EN400PC-10  | 100BASE-SX (SC) 1310nm Single-Mode Fiber Fast Ethernet Adapter (10km)                      |
| EN400PT     | 100BASE-FX Multi Mode (ST) Ethernet Adapter (Low profile)                                  |
| EN400PC-20  | 100BASE-FX Single Mode (SC) -20Km Ethernet Adapter (Low profile)                           |
| EN400PC-40  | 100BASE-FX Single Mode (SC) -40Km Ethernet Adapter (Low profile)                           |
| EN400PT-20  | 100BASE-FX Single Mode (ST) -20Km Ethernet Adapter (Low profile)                           |
| EN400PCA-20 | 100BASE-FX Single Mode (SC) WDM-TX :1310nm/RX :1550nm -20Km Ethernet Adapter (Low profile) |
| EN400PCB-20 | 100BASE-FX Single Mode (SC) WDM-TX :1550nm/RX :1310nm -20Km Ethernet Adapter (Low profile) |
| EN400PCA-40 | 100BASE-FX Single Mode (SC) WDM-TX :1310nm/RX :1550nm -40Km Ethernet Adapter (Low profile) |
| EN400PCB-40 | 100BASE-FX Single Mode (SC) WDM-TX :1550nm/RX :1310nm -40Km Ethernet Adapter (Low profile) |
| EN400PLC    | 100BASE-FX Multi Mode (LC) -2Km Ethernet Adapter (Low profile)                             |
| EN400PSFP   | 100BASE SFP Ethernet Adapter (Low profile)                                                 |



© EtherWAN Systems, Inc. All rights reserved. 20220721

EtherWAN is constantly developing and improving products. Specifications are subject to change without notice and without incurring any obligation.