

OttoE 08 FE

Industrial 8-port Fast Ethernet Unmanaged Switches



Overview

The **OttoE 08 FE** Series from EtherWAN is a compact, industrial-grade unmanaged Ethernet switch, built for reliable performance in space-constrained and harsh environments. Designed for simplicity and efficiency, it delivers essential Ethernet networking capabilities at a cost-effective price point.

Supporting a wide input voltage range of **9 to 55VDC** with redundant power options, the OttoE 08 FE also features a relay alarm to signal power failures. The switch offers multiple Fast Ethernet ports, with models available that include both copper and 100Mbps **SFP** ports for extended-distance connections.

With support for auto-negotiation (full/half duplex) and auto MDI/MDIX, device connection is straightforward and hassle-free. **QoS** (Quality of Service) functionality ensures traffic prioritization for optimized network performance. Housed in a rugged metal enclosure designed for DIN rail mounting, the OttoE 08 FE is built for easy installation and long-term durability—mounting kit included.

Deployment scenarios: Automation, Railway, Intelligent Intersection

IEC 62443-4-2 Compliance – Built and reviewed according to IEC 62443-4-1 secure development practices.

EtherWAN — "[When Connectivity is Crucial.](#)"

Highlight

+ Reliable Operation

Redundant dual power input 12/24/48 VDC

+ Rugged Design

Fanless design

+ SFP Connectivity

Up to two 100BASE SFP option

+ QoS Prioritized Messages

EtherNet/IP (UDP 2222)

Specifications

+ Interface

Ethernet

10/100BASE-TX: 6/8-ports

100BASE-SFP: 0/2-ports

Alarm Contact

One relay output with current 0.5A@30V

LED Indicators

Per Unit: Power 1 (Green), Power 2 (Green), Fault (Red)

Per Port: Link/Activity (Green)

+ Physical

Casing Material

Metal

IP Rating

IP40

Dimensions

45 x 75 x 100mm (W x D x H) (1.77" x 2.95" x 3.94")

Weight

336g (0.74lbs)

Installation Type

DIN-Rail (Top hat type 35mm) mounting

+ Technology

Standards

IEEE 802.3 10BASE-T

IEEE 802.3u 100BASE-TX/FX

IEEE 802.3az Energy Efficient Ethernet

IEEE 802.1p Quality of Service (QoS)

Forward/Filtering Rate

14,880pps for 10Mbps

148,810pps for 100Mbps

Packet Buffer Memory

768K bits

Processing Type

Store-and-Forward

Auto Negotiation

Half-duplex back-pressure

Auto MDI/MDIX

Address Table Size

2K MAC

+ Regulatory

ISO

Manufactured in ISO-9001 facility

EMI

FCC Part 15 Class A

VCCI Class A

EN 61000-6-4

ICES-003

EN 55032

BSMI

EMS

EN 61000-6-2

- EN 61000-4-2 (ESD)

- EN 61000-4-3 (Radiated RFI)

- EN 61000-4-4 (Burst)

- EN 61000-4-5 (Surge)

- EN 61000-4-6 (Induced RFI)

- EN 61000-4-8 (Magnetic field)

Safety

UL 61010

Cybersecurity

IEC 62443-4-1

IEC 62443-4-2

Environmental Test Compliance

IEC 60068-2-6 Fc (Vibration)

IEC 60068-2-27 Ea (Shock)

FED STD 101C Method 5007.1

(Free fall w/package)

Traffic

NEMA TS2

Railway

EN 50121-4

+ Power

Input

9-55VDC (Terminal Block)

Power Consumption

3.4W max.

Protection

Reverse Polarity Protection

+ Environmental

Operating Temp.

-10 to 60°C (14 to 140°F)

Storage Temp.

-40 to 85°C (-40 to 185°F)

Relative Humidity

5% to 95% (non-condensing)

+ Warranty

Length

Limited Lifetime

Details


www.etherwan.com/support/warranty-policy

+ What's Included


Device

Ethernet switch

Dimensions



Application



Ordering Info

+ Fast Ethernet models

				
	TF100-0800	TF100-0602	TF100(H)-0800	TF100(H)-0602
10/100Base TX	8	6	8	6
100Base SFP	-	2	-	2
Power Input	2 (9~55VDC) Push-in spring terminal block			
QoS	EtherNet/IP			
Corrosion Resistant	IP30		IP40	
Operating Temp.	-10 to 60°C		-40 to 75°C	
	Quote	Quote	Quote	Quote

+ Optional Accessories

HDR-30-24	30W/1.5A DIN-Rail 24VDC Hardened Power Supply
HDR-60-24	60W/2.5A DIN-Rail 24VDC Hardened Power Supply

100BASE SFP Modules	www.etherwan.com/products/sfp-fiber-transceiver
---------------------	--

