

OttoE 16 GE

Industrial 16-port Gigabit Unmanaged Ethernet Switches



Overview

The OttoE 16 GE Series from EtherWAN is a robust, unmanaged Ethernet switching solution engineered for reliable operation in space-constrained and demanding industrial environments. Designed for simplicity and cost-efficiency, it delivers core networking functionality essential for industrial applications.

The switch supports a wide input voltage range of **10 to 55VDC** with redundant power capability and includes a relay alarm to signal power failure events, enhancing system reliability.

Featuring auto-negotiation (full/half duplex) and auto MDI/MDIX, the OttoE 16 GE ensures seamless integration with diverse network devices. Built-in **QoS** (Quality of Service) enhances traffic management by enabling prioritization of critical data. The unit is housed in a rugged metal enclosure, DIN rail mountable for secure and straightforward installation—mounting kit included.

Deployment scenarios: Automation, Railway, Intelligent Intersection

IEC 62443-4-2 Compliance – Built and reviewed according to IEC 62443-4-1 secure development practices.

EtherWAN — "When Connectivity is Crucial."

Highlight

+ Reliable Operation

IEEE 802.3az Energy Efficient Ethernet
Power failure notification

+ Rugged Design

Fanless design (No moving parts)
Reverse Polarity Protection

+ Corrosion Resistant

IP30 design

+ QoS Prioritized Messages

EtherNet/IP (UDP 2222)
PROFINET (Ethertype 0x8892)

Specifications

+ Interface

Ethernet

10/100/1000BASE-TX: 16-ports

Alarm Contact

One relay output with current 0.5A@48V

LED Indicators

Per Unit: Power 1 (Green), Power 2 (Green), Fault (Red)

Per Port: Link/Activity (Green)

Per Port: Speed (Yellow)

+ Physical

Casing Material

Metal

IP Rating

IP30

Dimensions

80 x 91 x 100mm (W x D x H) (3.15" x 3.58" x 3.94")

Weight

502g (1.11lbs)

Installation Type

DIN-Rail (Top hat type 35mm) mounting

+ Technology

Standards

IEEE 802.3 10BASE-T

IEEE 802.3u 100BASE-TX/FX

IEEE 802.3az Energy Efficient Ethernet

IEEE 802.1p Quality of Service (QoS)

Forward/Filtering Rate

14,880pps for 10Mbps

148,810pps for 100Mbps

1,488,100pps for 1000Mbps

Packet Buffer Memory

2M bits

Processing Type

Store-and-Forward

Auto Negotiation

Half-duplex back-pressure

Auto MDI/MDIX

Address Table Size

8K MAC

+ Regulatory

ISO

Manufactured in ISO-9001 facility

EMI

FCC Part 15 Class A

VCCI Class A

EN 61000-6-4

ICES-003

EN 55032

BSMI

EMS

EN 61000-6-2

- EN 61000-4-2 (ESD)

- EN 61000-4-3 (Radiated RFI)

- EN 61000-4-4 (Burst)

- EN 61000-4-5 (Surge)

- EN 61000-4-6 (Induced RFI)

- EN 61000-4-8 (Magnetic field)

Safety

UL 61010

Cybersecurity

IEC 62443-4-1

IEC 62443-4-2

Environmental Test Compliance

IEC 60068-2-6 Fc (Vibration)

IEC 60068-2-27 Ea (Shock)

IEC 60068-2-31

(Free fall w/package)

Traffic

NEMA TS2

Railway

EN 50121-4

+ Power

Input

10-55VDC (Terminal Block)

Power Consumption

10.88W max.

Protection

Reverse Polarity Protection

+ Environmental

Operating Temp.

-10 to 60°C (14 to 140°F)

Storage Temp.

-40 to 85°C (-40 to 185°F)

Relative Humidity

5% to 95% (non-condensing)

+ Warranty

Length

Limited Lifetime

Details


www.etherwan.com/support/warranty-policy

+ What's Included


Device

Ethernet switch

Dimensions



Application



Ordering Info

+ Gigabit Ethernet models

	
	TG100-1600
10/100/1000BASE TX	16
100/1000BASE SFP	-
Power Input	2 (10 - 55VDC) Push-in spring terminal block
QoS	EtherNet/IP, Profinet
Corrosion Resistant	IP30
	Quote

+ Optional Accessories

HDR-30-24	30W/1.5A DIN-Rail 24VDC Hardened Power Supply
HDR-60-24	60W/2.5A DIN-Rail 24VDC Hardened Power Supply

