

EX19162A

Unmanaged 16-Port Gigabit PoE with 2-Port SFP
and 2-Port RJ45 Ethernet Switch



Product Highlights

Power over Ethernet

- Total PoE power budget of 250W to deliver sufficient power to all connected PoE devices
- Overloading protection
- Power and data over a single cable with gigabit speed capable of handling cameras with 4K resolution and higher and other high bandwidth devices

Overview

EtherWAN's EX19162A is a 20-port Gigabit Power over Ethernet switch with high performance and features suited for small-business and commercial environments. The EX19162A is equipped with 16 10/100/1000BASE-T(X) PoE+ ports along with 4 gigabit uplink ports (2 RJ45 and 2 SFP). With full wire speed throughput, port speeds up to gigabit for 4K cameras and higher, and a power budget of 250W, the EX19162A is the perfect solution for security.

Ordering Information

Model

EX19162A 18-port 10/100/1000BASE-T(X) (16 PoE) + 2 1000M SFP

* Rack mounting kit included.

Hardware Specifications

Interface		+
Ethernet	10/100/1000BASE-T(X): 18 ports 1000BASE SFP: 2 ports	
LED Indicators	Per Unit: Power Per Port PoE: Status Per Port Link: Link/Activity	
Reset Button	Restore factory default settings	
Technology		+
Standards	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3z 1000BASE-SX/1000BASE-LX IEEE 802.3x Full duplex and flow control IEEE 802.3af Power over Ethernet (PoE) IEEE 802.3at Power over Ethernet (PoE+)	
Switching Fabric	40Gbps	
MAC Table Size	8K	
Packet Buffer Memory	4Mb	
Forward and Filtering Rate	14,880pps for 10Mbps 148,880pps for 100Mbps 1,488,000pps for 1000Mbps	
Processing Type	Store-and-Forward Auto-Negotiation Half-duplex back-pressure full-duplex flow control Auto MDI/MDIX	
Power		+
Input	100-240VAC, 50/60Hz	
Power Consumption	Device: 20W (without PoE) PoE Power Budget: 250W	
Physical		+
Casing Material	Metal	
Dimensions	440 x 220 x 44mm (W x D x H) 17.3" x 8.66" x 1.73"	
Weight	6.6lbs (3kg)	
Installation Type	Rack mounting	
Environmental		+
Operating Temp.	0 to 50°C (32 to 122°F)	
Storage Temp.	-20 to 80°C (-4 to 176°F)	
Relative Humidity	10% to 90% (non-condensing)	
Regulatory		+
ISO	Manufactured in ISO-9001 facility	
EMI	FCC Part 15 Class A	
Safety	UL 62368-1	

Warranty		+
Length	3 Years	
Details	www.etherwan.com/support/warranty-policy	
What's Included		+
Device	Ethernet Switch	
Power	AC power cord	
Installation	Mounting brackets, screws	
Documentation	Quick Install Guide	

Dimensions

