

產品型錄

When Connectivity is Crucial



您最佳的網路建構合作夥伴
—— 益網科技

- ◆ 乙太網路交換器
- ◆ PoE系列乙太網路產品
- ◆ 光電轉換器

Full Product Lines

Our established product lines and customizable features are built to support the long-term health of your network. With hardened, industrial and commercial grade products, we have the right networking for nearly any communications challenge your network may face.

1

Ethernet Switches

EtherWAN offers a robust line of unmanaged and managed switches with Layer 2, Lite Layer 3 and Layer 3 capabilities. EtherWAN switches are deployed across a wide range of applications and industries, delivering stable and speedy data transfer year in and year out.

- 5 [Hardened & Industrial L2/L3 Ethernet](#)
- 9 [Hardened & Industrial Managed Ethernet](#)
- 12 [Hardened & Industrial Unmanaged Ethernet](#)



2

PoE Solutions

EtherWAN's PoE products deliver unprecedented levels of reliability and flexibility, with a broad range of products designed for harsh environments, all with the power output needed to support even the most demanding PoE powered devices.

- 17 [Managed Ethernet Switches](#)
- 19 [Unmanaged Ethernet Switches](#)
- 20 [Hardened & Industrial Media Converters](#)



3

Media Converters

EtherWAN's Ethernet media converter series offers a full range of Ethernet to fiber transceivers from multi-mode, single-mode, or WDM with multiple selections of distance, wavelength and connector type.

- 21 [Hardened & Industrial](#)
- 23 [Commercial](#)
- 25 [Multiple Channel Chassis](#)



4

Wireless

EtherWAN provides a full line of industrial grade gateways that are designed for critical infrastructure and industrial applications. They provide a secure, reliable connection to industrial controllers, process automation equipment and smart grid assets on third party sites or remote locations.

26 [Industrial IoT Cellular Device](#)



5

Accessories

EtherWAN provides a variety of accessory products to support our connectivity solutions. These include standard items such as mounting kits and racks, as well as specialized devices such as surge protectors, SFP transceivers, and an innovative backup solution.



- 29 [TransRack](#)
- 30 [Surge Protectors](#)
- 31 [SFP Transceivers](#)
- 37 [Mounting Kits](#)

強固級 & 工業級 L2 / L3 乙太網路交換器 >>

EN 50121-4

EN 50121-4

IEC 61850-3

EN 50121-4

OSPF
PIM-DM/SMOSPF
PIM-DM/SM

OSPF VRRP

OSPF VRRP
60W PoE DI/DO

	Layer 3	Layer 3	L2 / L3	L2 / L3
型 號	EG97244	EG97023	EX77900	EX75900
介 面				
總埠數	28	20	28	28
RJ45 埠 (10/100BASE-TX)	-	-	-	-
RJ45 埠 (10/100/1000BASE-T)	8	-	24	24
光纖埠 (100BASE-FX)	-	-	-	-
光纖埠 (Max. 100BASE-SFP)	-	-	-	-
光纖埠 (Max. 1000BASE-SX/LX/BX)	-	-	-	-
光纖埠 (Max. 1000BASE-SFP)	16	8	8	4
光纖埠 (Max. 10 Gigabit SFP+)	4	12	4	4
PoE 網路埠	-	-	-	24 (60W)
PoE 總供電瓦數	-	-	-	720W
RS-232 管理介面 / USB Console Port	√	√	√	√
告警介面	√	√	√	√
數位輸入	-	-	-	2
效 能				
MAC 地址表	24K	24K	16K	16K
緩衝記憶封包 (bits)	32M	32M	12M	12M
巨大封包 (bytes)	12K	12K	12K	9216
機 構				
機殼	金屬	金屬	金屬	金屬
安裝方式 *	R	R	R	R
安裝尺寸 (mm) (寬 x 深 x 高)	442 x 325 x 44	442 x 325 x 44	442 x 325 x 44	442 x 270 x 44.2
電 源				
電源輸入數	2	2	1 or 2	2
100 - 240VAC	√	√	√	-
Terminal Block	±48VDC	±48VDC	±48VDC	46-57VDC
環 境				
-10 to 60°C (14 to 140°F)	-	-	-	-
-40 to 75°C (-40 to 167°F)	√	√	√	√
網路備援				
Alpha-Ring / Alpha-Chain	-	-	√	√
STP / RSTP / MSTP	√	√	√	√
ITU-T G.8032 ERPS	√	√	-	-
網路管理及控制				
Layer 2	√	√	√	√
Layer 3 路由	√	√	√	√
法規標準				
CE / FCC / VCCI	√	√	√	√
IEC 61850-3 / IEEE 1613	-	-	√	-
EN 50155 / EN 50121-4	EN 50121-4	EN 50121-4	-	EN 50121-4
UL 508 / UL 61010	-	-	-	-
UL 60950 / UL 62368	UL 62368	UL 62368	UL 62368	UL 62368
BSMI	-	-	-	√
NEMA TS2	√	√	√	√
網路管理軟體				
eVue	√	√	√	√

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

強固級 & 工業級 L2 / L3 乙太網路交換器 >>

IEC 61850-3

EN 50121-4

OSPF VRRP
DI/DO IEEE 1588

IEC 61850-3

EN 50121-4

NEW

OSPF VRRP
DI/DO IEEE 1588

IEC 61850-3

EN 50121-4

NEW

OSPF VRRP 30W PoE
DI/DO IEEE 1588

型 號	L2 / L3 IG5 Rack	L2 / L3 IG5 L Rack	L2 / L3 IG5 SV
介 面			
總埠數	28	28	28
RJ45 埠 (10/100BASE-TX)	-	-	-
RJ45 埠 (10/100/1000BASE-T)	24	24	24
光纖埠 (100BASE-FX)	-	-	-
光纖埠 (Max. 100BASE-SFP)	24	24	24
光纖埠 (Max. 1000BASE-SX/LX/BX)	-	-	-
光纖埠 (Max. 1000BASE-SFP)	24	24	24
光纖埠 (Max. 10 Gigabit SFP+)	4	4	4
PoE 網路埠	-	-	8 (30W)
PoE 總供電瓦數	-	-	90W
RS-232 管理介面 / USB Console Port	√	√	√
告警介面	√	√	√
數位輸入	2	2	2
效 能			
MAC 地址表	16K	16K	16K
緩衝記憶體封包 (bits)	12M	12M	12M
巨大封包 (bytes)	9216	9216	9216
機 構			
機殼	金屬	金屬	金屬
安裝方式 *	R	R	R, P
安裝尺寸 (mm) (寬 x 深 x 高)	442 x 325 x 44	442 x 325 x 44	442 x 267 x 44
電 源			
電源輸入數	2	2	2
100 - 240VAC	√	√	-
Terminal Block	24 / ±48VDC, 88 - 300 VDC, 100-240 VAC	24 / ±48VDC, 88 - 300 VDC, 100-240 VAC	24 - 48VDC
環 境			
-10 to 60°C (14 to 140°F)	-	√	-
-40 to 75°C (-40 to 167°F)	√	-	√
網路備援			
Alpha-Ring / Alpha-Chain	√	√	√
STP / RSTP / MSTP	√	√	√
網路管理及控制			
Layer 2	√	√	√
Layer 3 路由	√	√	√
法規標準			
CE / FCC / VCCI	√	√	√
IEC 61850-3 / IEEE 1613	√	√	√
EN 50155 / EN 50121-4	EN 50121-4	EN 50121-4	EN 50121-4
UL 508 / UL 61010	-	-	-
UL 60950 / UL 62368	UL 62368	UL 62368	UL 62368
NEMA TS2	√	√	√
BSMI	√	√	√
網路管理軟體			
eVue	√	√	√

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

強固級 & 工業級 L2 / L3 乙太網路交換器 >>

EN 50121-4



NEW

90W PoE
OSPF VRRP

EN 50121-4

90W PoE
OSPF VRRP
DI/DO

EN 50121-4

60W PoE
OSPF VRRP
DI/DO90W PoE
OSPF VRRP
DI/DO

	L2 / L3	L2 / L3	L2 / L3	L2 / L3
型 號	EX78900G	EX78900X	EX78900E	EX78900H
介 面				
總埠數	12	16	16	16
RJ45 埠 (10/100BASE-TX)	-	-	-	-
RJ45 埠 (10/100/1000BASE-T)	8	12	12	12
光纖埠 (100BASE-FX)	-	-	-	-
光纖埠 (Max. 100BASE-SFP)	4	-	4	4
光纖埠 (Max. 1000BASE-SX/LX/BX)	-	-	-	-
光纖埠 (Max. 1000BASE-SFP)	4	4	4	4
光纖埠 (Max. 2.5 Gigabit SFP)	4	-	-	-
光纖埠 (Max. 10 Gigabit SFP+)	-	4	-	-
PoE 網路埠	8 (90W)	12 (90W)	12 (8 x 30W, 4 x 60W)	12 (90W)
PoE 總供電瓦數	480W / 400W	360W	240W	360W
RS-232 管理介面 / USB Console Port	√	√	√	√
告警介面	√	√	√	√
數位輸入	-	2	2	2
效 能				
MAC 地址表	16K	16K	16K	16K
緩衝記憶封包 (bits)	12M	12M	12M	12M
巨大封包 (bytes)	9216	9216	9216	9216
機 構				
機殼	金屬	金屬	金屬	金屬
安裝方式 *	D, P, W	D, P	D, P	D, P
安裝尺寸 (mm) (寬 x 深 x 高)	62 x 125 x 145	72 x 140 x 170	72 x 140 x 170	71.4 x 140 x 170
電 源				
電源輸入數	2	2	2	2
100 - 240VAC	-	-	-	-
Terminal Block	46 - 57VDC	46 - 57VDC	46 - 57VDC	46 - 57VDC
環 境				
-10 to 60°C (14 to 140°F)	-	-	-	-
-40 to 75°C (-40 to 167°F)	√	√	√	√
網路備援				
Alpha-Ring / Alpha-Chain	-	√	√	√
STP / RSTP / MSTP	√	√	√	√
ITU-T G.8032 ERPS	√	-	-	-
網路管理及控制				
Layer 2	√	√	√	√
Layer 3 路由	√	√	√	√
法規標準				
CE / FCC / VCCI	√	√	√	√
IEC 61850-3 / IEEE 1613	-	-	-	-
EN 50155 / EN 50121-4	EN 50121-4	EN 50121-4	EN 50121-4	-
UL 508 / UL 61010	-	-	UL 61010	UL 61010
UL 60950 / UL 62368	UL 62368	UL 62368	-	-
NEMA TS2	√	√	√	√
BSMI	√	√	√	-
網路管理軟體				
eVue	√	√	√	√

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

強固級 & 工業級 L2 / L3 乙太網路交換器 >>



	L2 / L3	L2 / L3
型 號	EX73900E	EX73900X
介 面		
總埠數	16	16
RJ45 埠 (10/100BASE-TX)	-	-
RJ45 埠 (10/100/1000BASE-T)	12	12
光纖埠 (100BASE-FX)	-	-
光纖埠 (Max. 100BASE-SFP)	-	-
光纖埠 (Max. 1000BASE-SX/LX/BX)	-	-
光纖埠 (Max. 1000BASE-SFP)	4	4
光纖埠 (Max. 10 Gigabit SFP+)	-	4
PoE 網路埠	-	-
PoE 總供電瓦數	-	-
RS-232 管理介面 / USB Console Port	√	√
告警介面	√	√
數位輸入	2	2
效 能		
MAC 地址表	16K	16K
緩衝記憶體封包 (bits)	12M	12M
巨大封包 (bytes)	9216	9216
機 構		
機殼	金屬	金屬
安裝方式 *	D, P	D, P
安裝尺寸 (mm) (寬 x 深 x 高)	72 x 140 x 170	72 x 140 x 170
電 源		
電源輸入數	2	2
100 - 240VAC	-	-
Terminal Block	12 - 48VDC	12 - 48VDC
環 境		
-10 to 60°C (14 to 140°F)	-	-
-40 to 75°C (-40 to 167°F)	√	√
網路備援		
Alpha-Ring / Alpha-Chain	√	√
STP / RSTP / MSTP	√	√
網路管理及控制		
Layer 2	√	√
Layer 3 路由	√	√
法規標準		
CE / FCC / VCCI	√	√
IEC 61850-3 / IEEE 1613	√	√
EN 50155 / EN 50121-4	EN 50121-4	EN 50121-4
UL 508 / UL 61010	UL 61010	UL 61010
UL 60950 / UL 62368	-	-
NEMA TS2	√	√
BSMI	√	√
網路管理軟體		
eVue	√	√

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

強固級 & 工業級網管型乙太網路交換器 >>



型 號	EX87000	EX27000	EX77000	EX8000	EX83304
介 面					
總埠數	28	28	28	12	16
RJ45 埠 (10/100BASE-TX)	24	24	24	8	12
RJ45 埠 (10/100/1000BASE-T)	4	4	4	2	-
光纖埠 (100BASE-FX)	24	24	24	4	-
光纖埠 (Max. 100BASE-SFP)	24	24	24	2	-
光纖埠 (Max. 1000BASE-SX/LX/BX)	4	4	4	2	-
光纖埠 (Max. 1000BASE-SFP)	4	4	4	2	4
光纖埠 (Max. 10 Gigabit SFP+)	-	-	-	-	-
PoE 網路埠	-	-	-	8 (60W)	-
PoE 總供電瓦數	-	-	-	360W	-
RS-232 管理介面 / USB Console Port	√	√	√	√	√
告警介面	-	-	-	√	√
效 能					
MAC 地址表	16K	16K	16K	16K	16K
緩衝記憶封包 (bits)	12M	12M	12M	12M	12M
巨大封包 (bytes)	9216	9216	9216	-	9216
機 構					
機殼	金屬	金屬	金屬	金屬	金屬
安裝方式 *	R	R	R	D, P	D, P
安裝尺寸 (mm) (寬 x 深 x 高)	442 x 375 x 44	Redundant Power: 442 x 375 x 44 Single Power: 442 x 284 x 44.2	Redundant Power: 442 x 375 x 44 Single Power: 442 x 250 x 44.2	71.4 x 140 x 170	72 x 140 x 170
電 源					
電源輸入數	1 or 2	1 or 2	1 or 2	2	2
100 - 240VAC	√	√	√	-	-
Terminal Block	±48VDC, 88 - 370VDC	±48VDC, 88 - 370VDC	±48VDC, 88 - 370VDC	54 - 57VDC	12 - 48VDC
環 境					
-10 to 60°C (14 to 140°F)	-	√	-	-	-
-40 to 75°C (-40 to 167°F)	√	-	√	√	√
網路備援					
Alpha-Ring / Alpha-Chain	√	√	√	√	√
STP / RSTP / MSTP	√	√	√	√	√
網路管理及控制					
Layer 2	√	√	√	√	√
Layer 3 路由	-	-	-	-	-
法規標準					
CE / FCC / VCCI	√	√	√	√	√
IEC 61850-3 / IEEE 1613	√	√	-	-	√
EN 50155 / EN 50121-4	EN 50121-4	EN 50121-4	-	-	-
UL 508 / UL 61010	-	-	-	UL 61010	UL 61010
UL 60950 / UL 62368	UL 62368	UL 62368	UL 62368	-	-
NEMA TS2	√	-	√	√	-
網路管理軟體					
eVue	√	√	√	√	√

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

** 提供監測模式及支援部份功能

強固級 & 工業級網管型乙太網路交換器 >>

EN 50121-4



型 號	EX71000	SmartE SG300
介 面		
總埠數	10	8, 16
RJ45 埠 (10/100BASE-TX)	8	-
RJ45 埠 (10/100/1000BASE-T)	2	8, 16
光纖埠 (100BASE-FX)	4	-
光纖埠 (Max. 100BASE-SFP)	4	2, 4
光纖埠 (Max. 1000BASE-SX/LX/BX)	2	-
光纖埠 (Max. 1000BASE-SFP)	2	2, 4
光纖埠 (Max. 10 Gigabit SFP+)	-	-
PoE 網路埠	-	-
PoE 總供電瓦數	-	-
RS-232 管理介面 / USB Console Port	-	-
告警介面	√	√
效 能		
MAC 地址表	16K	8K
緩衝記憶體封包 (bits)	12M	4M
巨大封包 (bytes)	-	9216
機 構		
機殼	金屬	金屬
安裝方式 *	D, P, R	D, P, W
安裝尺寸 (mm) (寬 x 深 x 高)	60x 125x 145mm	8-port: 45 x 125.5 x 130 16-port: 85 x 125.5 x 130
電 源		
電源輸入數	2	2
100 - 240VAC	-	-
Terminal Block	12 - 48VDC	12 - 57VDC
環 境		
-10 to 60°C (14 to 140°F)	-	-
-40 to 75°C (-40 to 167°F)	√	√
網路備援		
Alpha-Ring / Alpha-Chain	√	LTS / FRD
STP / RSTP / MSTP	√	STP / RSTP / MRP
網路管理及控制		
Layer 2	√	√
Layer 3 路由	-	-
法規標準		
CE / FCC / VCCI	√	√
IEC 61850-3 / IEEE 1613	-	-
EN 50155 / EN 50121-4	-	-
UL 508 / UL 61010	UL 61010	UL 61010
UL 60950 / UL 62368	-	-
NEMA TS2	-	-
網路管理軟體		
eVue	√**	√**

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

** 提供監測模式及支援部份功能

強固級 & 工業級網管型乙太網路交換器 >>

ISA 12.12.01

EN 50121-4



型 號	EX73000	EX63000	EX61000A
介 面			
總埠數	18	18	10
RJ45 埠 (10/100BASE-TX)	16	16	8
RJ45 埠 (10/100/1000BASE-T)	2	2	2
光纖埠 (100BASE-FX)	-	-	4
光纖埠 (Max. 100BASE-SFP)	-	-	4
光纖埠 (Max. 1000BASE-SX/LX/BX)	2	2	2
光纖埠 (Max. 1000BASE-SFP)	-	-	2
光纖埠 (Max. 10 Gigabit SFP+)	-	-	-
PoE 網路埠	-	-	-
PoE 總供電瓦數	-	-	-
RS-232 管理介面 / USB Console Port	√	√	√
告警介面	√	-	√
效 能			
MAC 地址表	16K	16K	16K
緩衝記憶體封包 (bits)	12M	12M	12M
巨大封包 (bytes)	-	-	-
機 構			
機殼	金屬	金屬	金屬
安裝方式 *	D, P	D, P, R	D, P, R
安裝尺寸 (mm) (寬 x 深 x 高)	65 x 125 x 45	59 x 125 x 45	54 x 125 x 145
電 源			
電源輸入數	2	2	2
100 - 240VAC	-	-	-
Terminal Block	12 - 48VDC	12 - 48VDC	12 - 48VDC
環 境			
-10 to 60°C (14 to 140°F)	-	√	√
-40 to 75°C (-40 to 167°F)	√	-	-
網路備援			
Alpha-Ring / Alpha-Chain	√	√	√
STP / RSTP / MSTP	√	√	√
網路管理及控制			
Layer 2	√	√	√
Layer 3 路由	-	-	-
法規標準			
CE / FCC / VCCI	√	√	√
ISA 12.12.01	√	-	-
IEC 61850-3 / IEEE 1613	-	-	-
EN 50155 / EN 50121-4	-	-	EN 50121-4
UL 508 / UL 61010	UL 61010	UL 61010	UL 61010
UL 60950 / UL 62368	-	-	-
NEMA TS2	-	-	-
網路管理軟體			
eVue	√	√	√

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

強固級 & 工業級非網管乙太網路交換器 >>

EN 50121-4

NEW

EN 50121-4

NEW

EN 50121-4

NEW



型 號	OttoE 05 GE	OttoE 08(H) FE	OttoE 08(H) GE
介 面			
總埠數	5	8	8
RJ45 埠 (10/100BASE-TX)	-	8	-
RJ45 埠 (10/100/1000BASE-T)	5	-	8
光纖埠 (100BASE-FX)	-	-	-
光纖埠 (Max. 100BASE-SFP)	-	2	-
光纖埠 (Max. 1000BASE-SX/LX/BX)	-	-	-
光纖埠 (Max. 1000BASE-SFP)	-	-	2
PoE 網路埠	-	-	-
PoE 總供電瓦數	-	-	-
RS-232 管理介面 / USB Console Port	-	-	-
告警介面	-	√	-
效 能			
MAC 地址表	2K	2K	4K
緩衝記憶體封包 (bits)	1M	768K	1.5M
巨大封包 (bytes)	9216	-	-
機 構			
機殼	塑膠	金屬	金屬
安裝方式 *	D, P	D	D
安裝尺寸 (mm) (寬 x 深 x 高)	25 x 81 x 100	45 x 75 x 100	45 x 75 x 100
電 源			
電源輸入數	1	2	2
100 - 240VAC	-	-	-
Terminal Block	9 - 55VDC	9 - 55VDC	9 - 55VDC
環 境			
-10 to 60°C (14 to 140°F)	√	√	√
-40 to 75°C (-40 to 167°F)	-	√	√
網路備援			
Alpha-Ring / Alpha-Chain	-	-	-
STP / RSTP / MSTP	-	-	-
網路管理及控制			
Layer 2	-	-	-
QoS	Ethernet/IP, Profinet	Ethernet/IP	Profinet
法規標準			
CE / FCC / VCCI	√	√	√
NEMA TS2	-	√	√
EN 50155 / EN 50121-4	EN 50121-4	EN 50121-4	EN 50121-4
UL 508 / UL 61010	UL 61010	UL 61010	UL 61010
BSMI	√	√	√

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

強固級 & 工業級非網管乙太網路交換器 >>

EN 50121-4 NEW

EN 50121-4 NEW



型 號	OttoE 16(H) FE	OttoE 16 GE
介 面		
總埠數	16	16
RJ45 埠 (10/100BASE-TX)	16	-
RJ45 埠 (10/100/1000BASE-T)	-	16
光纖埠 (100BASE-FX)	-	-
光纖埠 (Max. 100BASE-SFP)	2	-
光纖埠 (Max. 1000BASE-SX/LX/BX)	-	-
光纖埠 (Max. 1000BASE-SFP)	-	-
PoE 網路埠	-	-
PoE 總供電瓦數	-	-
RS-232 管理介面 / USB Console Port	-	-
告警介面	√	√
效 能		
MAC 地址表	8K	8K
Packet Buffer Memory (bits)	2M	2M
Jumbo Frame (bytes)	9216	9216
機 構		
機殼	金屬	金屬
安裝方式 *	D	D
安裝尺寸 (mm) (寬 x 深 x 高)	80 x 91 x 100	80 x 91 x 100
電 源		
電源輸入數	2	2
100 - 240VAC	-	-
Terminal Block	9 - 55VDC	9 - 55VDC
環 境		
-10 to 60°C (14 to 140°F)	√	√
-40 to 75°C (-40 to 167°F)	√	-
網路備援		
Alpha-Ring / Alpha-Chain	-	-
STP / RSTP / MSTP	-	-
網路管理及控制		
Layer 2	-	-
QoS	Ethernet/IP	Ethernet/IP, Profinet
法規標準		
CE / FCC / VCCI	√	√
ISA 12.12.01	-	-
ATEX	-	-
NEMA TS2	-	-
EN 50155 / EN 50121-4	EN 50121-4	EN 50121-4
UL 508 / UL 61010	UL 61010	UL 61010
BSMI	√	√

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

強固級 & 工業級非網管乙太網路交換器 >>

EN 50121-4

NEW



90W PoE

EN 50121-4

NEW



90W PoE

型 號	OttoE PoE 08(H) GE	OttoE PoE 10(H) GE
介 面		
總埠數	8	10
RJ45 埠 (10/100BASE-TX)	-	-
RJ45 埠 (10/100/1000BASE-T)	8	8
光纖埠 (100BASE-FX)	-	-
光纖埠 (Max. 100BASE-SFP)	-	-
光纖埠 (Max. 1000BASE-SX/LX/BX)	-	-
光纖埠 (Max. 1000BASE-SFP)	-	2
PoE 網路埠	8	4
PoE 總供電瓦數	270W	270W
RS-232 管理介面 / USB Console Port	-	-
告警介面	-	√
效 能		
MAC 地址表	4K	4K
Packet Buffer Memory (bits)	1.5M	1.5M
Jumbo Frame (bytes)	9216	9216
機 構		
機殼	金屬	金屬
安裝方式 *	D	D
安裝尺寸 (mm) (寬 x 深 x 高)	45 x 125 x 145	45 x 125 x 145
電 源		
電源輸入數	2	2
100 - 240VAC	-	-
Terminal Block	46 - 57VDC	46 - 57VDC
環 境		
-10 to 60°C (14 to 140°F)	√	√
-40 to 75°C (-40 to 167°F)	√	√
網路備援		
Alpha-Ring / Alpha-Chain	-	-
STP / RSTP / MSTP	-	-
網路管理及控制		
Layer 2	-	-
QoS	Ethernet/IP, Profinet	Ethernet/IP, Profinet
法規標準		
CE / FCC / VCCI	√	√
NEMA TS2	√	√
EN 50155 / EN 50121-4	EN 50121-4	EN 50121-4
UL 508 / UL 61010	UL 61010	UL 61010
BSMI	√	√

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

強固級 & 工業級非網管乙太網路交換器 >>



型 號	EX42000	EX32008
介 面		
總埠數	5	8
RJ45 埠 (10/100BASE-TX)	5	8
RJ45 埠 (10/100/1000BASE-T)	-	-
光纖埠 (100BASE-FX)	1	-
光纖埠 (Max. 100BASE-SFP)	-	-
光纖埠 (Max. 1000BASE-SX/LX/BX)	-	-
光纖埠 (Max. 1000BASE-SFP)	-	-
PoE 網路埠	-	-
PoE 總供電瓦數	-	-
RS-232 管理介面 / USB Console Port	-	-
告警介面	√	-
效 能		
MAC 地址表	1K	1K
Packet Buffer Memory (bits)	-	448K
Jumbo Frame (bytes)	-	-
機 構		
機殼	塑膠	塑膠
安裝方式 *	D	D
安裝尺寸 (mm) (寬 x 深 x 高)	26 x 70 x 100	36 x 86 x 149
電 源		
電源輸入數	1	2
100 - 240VAC	-	-
Terminal Block	12 - 48VDC	12 - 48VDC
環 境		
-10 to 60°C (14 to 140°F)	√	√
-40 to 75°C (-40 to 167°F)	-	-
網路備援		
Alpha-Ring / Alpha-Chain	-	-
STP / RSTP / MSTP	-	-
網路管理及控制		
Layer 2	-	-
Layer 3 Routing	-	-
法規標準		
CE / FCC / VCCI	√	√
IEC 61850-3 / IEEE 1613	-	-
EN 50155 / EN 50121-4	-	-
UL 508 / UL 61010	-	-
UL 60950 / UL 62368	-	√

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

強固級 & 工業級非網管乙太網路交換器 >>



型 號	EX43008	EX46900A
介 面		
總埠數	8	10
RJ45 埠 (10/100BASE-TX)	8	-
RJ45 埠 (10/100/1000BASE-T)	-	8
光纖埠 (100BASE-FX)	-	1
光纖埠 (Max. 100BASE-SFP)	-	-
光纖埠 (Max. 1000BASE-SX/LX/BX)	-	2
光纖埠 (Max. 1000BASE-SFP)	-	2
Max. 10 Gigabit SFP+	-	2
PoE 網路埠	-	8 (30W)
PoE 總供電瓦數	-	120W
RS-232 管理介面 /USB Console Port	-	√
告警介面	√	√
效 能		
MAC 地址表	1K	8K
Packet Buffer Memory (bits)	448K	4M
機 構		
機殼	金屬	金屬
安裝方式 *	D	Desktop, W, D
安裝尺寸 (mm) (寬 x 深 x 高)	43.6 x 110 x 135	66.8 x 125 x 145mm
電 源		
電源輸入數	2	2
Terminal Block	12 - 48VDC	18 - 57VDC
環 境		
-10 to 60°C (14 to 140°F)	√	-
-40 to 75°C (-40 to 167°F)	-	√
網路備援		
Alpha-Ring / Alpha-Chain	-	√
STP / RSTP / MSTP	-	-
網路管理及控制		
Layer 2	-	√
Layer 3 Routing	-	-
法規標準		
CE / FCC / VCCI	√	√
IEC 61850-3 / IEEE 1613	-	-
EN 50155 / EN 50121-4	-	-
UL 508 / UL 61010	-	-
UL 60950 / UL 62368	√	-

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

網管型乙太網路交換器 >>

EN 50121-4

EN 50121-4

EN 50121-4

NEW

90W PoE
OSPF VRRP60W PoE
OSPF VRRP
DI/DO90W PoE
OSPF VRRP
DI/DO90W PoE
OSPF VRRP
DI/DO

60W PoE

型 號	EX78900G	EX78900E	EX78900X	EX78900H	EX78000
介 面					
總埠數	12	16	16	12	12
RJ45 埠 (10/100BASE-TX)	-	-	-	-	8
RJ45 埠 (10/100/1000BASE-T)	8	12	12	2	2
光纖埠 (100BASE-FX)	-	-	-	-	4
光纖埠 (Max. 100BASE-SFP)	4	4	-	4	2
光纖埠 (Max. 1000BASE-SX/LX/BX)	-	-	-	-	2
光纖埠 (Max. 1000BASE-SFP)	4	4	4	4	2
光纖埠 (Max. 2.5 Gigabit SFP)	4	-	-	-	-
光纖埠 (Max. 10 Gigabit SFP+)	-	-	4	-	-
PoE 網路埠	8 (90W)	12 (8 x 30W, 4 x 60W)	12 (90W)	12 (90W)	8 (60W)
PoE 總供電瓦數	480W / 400W	240W	360W	360W	360W
RS-232 管理介面	√	√	√	√	√
告警介面	√	√	√	√	√
數位輸入	-	2	2	-	-
效 能					
MAC 地址表	16K	16K	16K	16K	16K
緩衝記憶封包 (bits)	4M	12M	12M	12M	12M
巨大封包 (bytes)	9216	9216	9216	9216	-
機 構					
機殼	金屬	金屬	金屬	金屬	金屬
安裝方式 *	D, P, W	D, P	D, P	D, P	D, P
安裝尺寸 (mm) (寬 x 深 x 高)	62 x 125 x 145	72 x 140 x 170	72 x 140 x 170	71.4 x 140 x 170	71.4 x 140 x 170
電 源					
電源輸入數	2	2	2	2	2
100 - 240VAC	-	-	-	-	-
Terminal Block	46 - 57VDC	46 - 57VDC	46 - 57VDC	46 - 57VDC	52 - 57VDC
環 境					
-10 to 60°C (14 to 140°F)	-	-	-	-	-
-40 to 75°C (-40 to 167°F)	√	√	√	√	√
網路備援					
Alpha-Ring / Alpha-Chain	-	√	√	√	√
STP / RSTP / MSTP	√	√	√	√	√
ITU-T G.8032 ERPS	√	-	-	-	-
網路管理及控制					
Layer 2	√	√	√	√	√
Layer 3 路由	√	√	√	√	-
法規標準					
CE / FCC / VCCI	√	√	√	√	√
IEC 61850-3 / IEEE 1613	-	-	-	-	-
EN 50155 / EN 50121-4	EN 50121-4	EN 50121-4	EN 50121-4	-	-
UL 508 / UL 61010	-	UL 61010	UL 61010	UL 61010	UL 61010
UL 60950 / UL 62368	UL 62368	-	-	-	-
NEMA TS2	√	√	√	√	√
BSMI	√	√	√	-	-
網路管理軟體					
eVue	√	√	√	√	√

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

** 提供監測模式及支援部份功能

網管型乙太網路交換器 >>

IEC 61850-3

EN 50121-4

EN 50121-4

NEW

OSPF VRRP

OSPF VRRP

DI/DO IEEE 1588 30W PoE

60W PoE DI/DO



型 號	IG5-SV	EX75900	EX26262F
介 面			
總埠數	28	28	26
RJ45 埠 (10/100BASE-TX)	-	-	-
RJ45 埠 (10/100/1000BASE-T)	24	24	24
光纖埠 (100BASE-FX)	-	-	-
光纖埠 (Max. 100BASE-SFP)	24	-	-
光纖埠 (Max. 1000BASE-SX/LX/BX)	-	-	-
光纖埠 (Max. 1000BASE-SFP)	24	4	2 (Combo)
光纖埠 (Max. 10 Gigabit SFP+)	4	4	-
PoE 網路埠	8 (30W)	24 (60W)	24 (30W)
PoE 總供電瓦數	90W	720W	370W
RS-232 管理介面	√	√	-
告警介面	√	√	-
數位輸入	2	2	-
效 能			
MAC 地址表	16K	16K	8192
緩衝記憶體封包 (bits)	12M	12M	512K
巨大封包 (bytes)	9216	9216	9216
機 構			
機殼	金屬	金屬	金屬
安裝方式 *	R, P	R	R
安裝尺寸 (mm) (寬 x 深 x 高)	442 x 267 x 44	442 x 270 x 44.2	442 x 211 x 44
電 源			
電源輸入數	2	2	1
100 - 240VAC	-	-	√
Terminal Block	24 - 48VDC	52 - 57VDC	-
環 境			
-10 to 60°C (14 to 140°F)	-	-	√
-40 to 75°C (-40 to 167°F)	√	√	-
網路備援			
Alpha-Ring / Alpha-Chain	√	√	-
STP / RSTP / MSTP	√	√	√
網路管理及控制			
Layer 2	√	√	√
Layer 3 路由	√	√	-
法規標準			
CE / FCC / VCCI	√	√	√
IEC 61850-3 / IEEE 1613	√	-	-
EN 50155 / EN 50121-4	EN 50121-4	EN 50121-4	-
UL 508 / UL 61010	-	-	-
UL 60950 / UL 62368	UL 62368	UL 62368	UL 60950
BSMI	√	√	-
NEMA TS2	√	√	-
網路管理軟體			
eVue**	√	√	√

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

** 提供監測模式及支援部份功能

非網管型乙太網路交換器 >>

EN 50121-4

NEW



EN 50121-4

NEW



型 號	OttoE PoE 08(H) GE	OttoE PoE 10(H) GE	EX46900A
介 面			
總埠數	8	10	10
RJ45 埠 (10/100BASE-TX)	-	-	-
RJ45 埠 (10/100/1000BASE-T)	8	8	8
光纖埠 (100BASE-FX)	-	-	-
光纖埠 (Max. 100BASE-SFP)	-	-	-
光纖埠 (Max. 1000BASE-SX/LX/BX)	-	-	2
光纖埠 (Max. 1000BASE-SFP)	-	2	2
PoE 網路埠	8	4	8 (30W)
PoE 總供電瓦數	270W	270W	120W
RS-232 管理介面 / USB Console Port	-	-	-
告警介面	-	√	√
效 能			
MAC 地址表	4K	4K	8192
緩衝記憶封包 (bits)	1.5M	1.5M	4M
巨大封包 (bytes)	9216	9216	9.6K
機 構			
機殼	金屬	金屬	金屬
安裝方式 *	D	D	D
安裝尺寸 (mm) (寬 x 深 x 高)	45 x 125 x 145	45 x 125 x 145	66.8 x 125 x 145
電 源			
電源輸入數	2	2	2
100 - 240VAC	-	-	-
Terminal Block	46 - 57VDC	46 - 57VDC	18 - 57VDC
環 境			
-10 to 60°C (14 to 140°F)	√	√	-
-40 to 75°C (-40 to 167°F)	√	√	√
網路備援			
Alpha-Ring / Alpha-Chain	-	-	-
STP / RSTP / MSTP	-	-	-
網路管理及控制			
Layer 2	-	-	-
QoS	Ethernet/IP, Profinet	Ethernet/IP, Profinet	-
法規標準			
E Mark	-	-	√
CE / FCC / VCCI	√	√	√
ISA 12.12.01 / UL 1604	-	-	-
NEMA TS2	√	√	-
BSMI	√	√	-
EN 50155 / EN 50121-4	EN 50121-4	EN 50121-4	-
UL 508 / UL 61010	UL 61010	UL 61010	UL 508
UL 60950 / UL 62368	-	-	-

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

強固級 & 工業級光電轉換器 >>



型 號	EL2242	EL1032T
介 面		
RJ45 埠 (100BASE-T)	-	-
RJ45 埠 (10/100BASE-TX)	-	1
RJ45 埠 (1000BASE-T)	-	-
RJ45 埠 (10/100/1000BASE-T)	1	-
光纖埠 (100BASE-FX/BX WDM)	-	1
光纖埠 (100BASE-SFP)	1	-
光纖埠 (1000BASE-SX/LX/BX)	-	-
光纖埠 (1000BASE-SFP)	1	-
PoE 網路埠	PSE (30W)	PSE (30W)
網頁管理	-	-
告警介面	√	-
效 能		
Auto-negotiation, MDI/MDI-X 自動協調	√	√
流量控制	√	√
儲存與轉發	-	√
Link Fault Pass Through	√	√
機 構		
機殼	金屬	金屬
安裝方式 *	D	D, P
安裝尺寸 (mm) (寬 x 深 x 高)	42 x 90 x 100	70 x 110 x 30
電 源		
電源輸入數	2	2
Terminal Block	48 - 57VDC	48 - 57VDC
DC Jack	-	48VDC
AC to DC Adapter	-	-
環 境		
-10 to 60°C (14 to 140°F)	-	√
-40 to 75°C (-40 to 167°F)	√	-
法規標準		
CE / FCC / VCCI	√	√
ISA 12.12.01 / UL 1604	-	-
IEC 61850-3	-	-
EN 50121-4	-	-
UL 508 / UL 61010	-	-
UL/cUL 60950-1	√	-

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

強固級 & 工業級光電轉換器 >>



型 號	EL8020	EL8100	EL8000
介 面			
RJ45 埠 (100BASE-T)	-	-	-
RJ45 埠 (10/100BASE-TX)	-	-	-
RJ45 埠 (1000BASE-T)	-	-	1
RJ45 埠 (10/100/1000BASE-T)	1	1	-
光纖埠 (100BASE-FX/BX WDM)	-	-	-
光纖埠 (100BASE-SFP)	-	-	-
光纖埠 (1000BASE-SX/LX/BX)	-	1	1
光纖埠 (1000BASE-SFP)	1	-	1
PoE 網路埠	-	-	-
網頁管理	-	-	-
告警介面	√	√	√
效 能			
Auto-negotiation, MDI/MDI-X 自動協調	√	√	√
流量控制	-	-	-
儲存與轉發	-	-	-
Link Fault Pass Through	√	√	√
機 構			
機殼	Metal	Metal	Metal
安裝方式 *	D	D	D
安裝尺寸 (mm) (寬 x 深 x 高)	35.8 x 90 x 100	35.8 x 90 x 100	35.8 x 90 x 100
電 源			
電源輸入數	2	2	2
Terminal Block	12 - 48VDC	12 - 48VDC	12 - 48VDC
DC Jack	-	-	-
AC to DC Adapter	-	-	-
環 境			
-10 to 60°C (14 to 140°F)	-	-	-
-40 to 75°C (-40 to 167°F)	√	√	√
法規標準			
CE / FCC / VCCI	√	√	√
ISA 12.12.01 / UL 1604	-	-	-
EN 50121-4	-	-	-
UL 508 / UL 61010	UL 61010	UL 61010	UL 61010
UL/cUL 60950-1	-	-	-

* D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

強固級 & 工業級光電轉換器 >>

IEC 61850-3
EN 50121-4

ISA 12.12.01

IEC 61850-3
EN 50121-4

型 號	EL1142	EL900	EL1141	EX42011
介 面				
RJ45 埠 (100BASE-T)	-	-	-	-
RJ45 埠 (10/100BASE-TX)	2	1	1	1
RJ45 埠 (1000BASE-T)	-	-	-	-
RJ45 埠 (10/100/1000BASE-T)	-	-	-	-
光纖埠 (100BASE-FX/BX WDM)	2	1	1	1
光纖埠 (100BASE-SFP)	-	-	-	-
光纖埠 (1000BASE-SX/LX/BX)	-	-	-	-
光纖埠 (1000BASE-SFP)	-	-	-	-
PoE 網路埠	-	-	-	-
網頁管理	-	-	-	-
告警介面	√	√	√	-
效 能				
Auto-negotiation, MDI/MDI-X 自動協調	√	√	√	√
流量控制	√	√	√	√
儲存與轉發	√	√	√	√
Link Fault Pass Through	√	√	√	-
機 構				
機殼	金屬	金屬	金屬	塑膠
安裝方式 *	D	D, P	D	D
安裝尺寸 (mm) (寬 x 深 x 高)	50 x 110 x 135	50 x 110 x 135	50 x 110 x 135	26 x 110 x 70
電 源				
電源輸入數	2	2 / 1	3	1
Terminal Block	12 - 48VDC	10 - 48VDC	12 - 48VDC	12 - 48VDC
DC Jack	-	12VDC	12VDC	-
AC to DC Adapter	-	-	-	-
環 境				
-10 to 60°C (14 to 140°F)	-	-	-	√
-40 to 75°C (-40 to 167°F)	√	√	√	-
法規標準				
CE / FCC / VCCI	√	√	√	√
ISA 12.12.01 / UL 1604	-	√	-	-
IEC 61850-3	√	-	√	-
EN 50121-4	√	-	√	-
UL 508 / UL 61010	UL 61010	-	UL 508	-
UL/cUL 60950-1 / UL62368-1	-	√	UL62368-1	√

* C: 收容機箱 D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

企業級光電轉換器 >>



型 號	EL2211	EL2315
介 面		
RJ45 埠 (100BASE-T)	-	-
RJ45 埠 (10/100BASE-TX)	-	-
RJ45 埠 (1000BASE-T)	-	-
RJ45 埠 (10/100/1000BASE-T)	1	1
光纖埠 (100BASE-FX/BX WDM)	-	-
光纖埠 (100BASE-SFP)	-	1
光纖埠 (1000BASE-SX/LX/BX)	1	-
光纖埠 (1000BASE-SFP)	-	1
PoE 網路埠	-	-
網頁管理	-	-
告警介面	-	-
操作模式		
Auto-negotiation,MDI/MDI-X 自動協調	√	√
流量控制	√	√
儲存與轉發	√	√
Link Fault Pass Through	√	√
機 構		
機殼	金屬	金屬
安裝方式 *	C, W	C, W
安裝尺寸 (mm) (寬 x 深 x 高)	80.3 x 109.2 x 23.8	80.3 x 109.2 x 23.8
電 源		
電源輸入數	1	1
Terminal Block	-	-
DC Jack	12VDC	12VDC
AC to DC Adapter	√	√
環 境		
0 to 50°C (32 to 122°F)	√	√
-10 to 60°C (14 to 140°F)	-	-
法規標準		
CE / FCC / VCCI	√	√
ISA 12.12.01 / UL 1604	-	-
EN 50121-4	-	-
UL 508 / UL 61010	-	-
UL/cUL 60950-1/UL62368-1	UL62368-1	UL62368-1

* C: 收容機箱 D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

企業級光電轉換器 >>



型 號	EL100	EL200
介 面		
RJ45 埠 (100BASE-T)	-	-
RJ45 埠 (10/100BASE-TX)	1	1
RJ45 埠 (1000BASE-T)	-	-
RJ45 埠 (10/100/1000BASE-T)	-	-
光纖埠 (100BASE-FX/BX WDM)	1 FX	1 WDM
光纖埠 (100BASE-SFP)	-	-
光纖埠 (1000BASE-SX/LX/BX)	-	-
光纖埠 (1000BASE-SFP)	-	-
PoE 網路埠	-	-
網頁管理	-	-
告警介面	-	-
操作模式		
MDI/MDI-X 自動協調	√	√
流量控制	√	√
儲存與轉發	√	√
Link Fault Pass Through	√	√
機 構		
機殼	金屬	金屬
安裝方式 *	C, W	C, W
安裝尺寸 (mm) (寬 x 深 x 高)	80.3 x 109.2 x 23.8	80.3 x 109.2 x 23.8
電 源		
電源輸入數	1	1
Terminal Block	-	-
DC Jack	12VDC	12VDC
AC to DC Adapter	√	√
環 境		
0 to 45°C (32 to 113°F)	√	√
-10 to 60°C (14 to 140°F)	-	-
法規標準		
CE / FCC / VCCI	√	√
ISA 12.12.01 / UL 1604	-	-
EN 50121-4	-	-
UL 508 / UL 61010	-	-
UL/cUL 60950-1/UL62368-1	UL62368-1	UL62368-1

* C: 收容機箱 D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

多埠型光電轉換器收容機箱 >>



型 號	EMC1600	EMC400
介 面		
RJ45 埠 (100BASE-T)	16	4
RJ45 埠 (10/100BASE-TX)	16	4
RJ45 埠 (1000BASE-T)	16	4
RJ45 埠 (10/100/1000BASE-T)	16	4
光纖埠 (100BASE-FX/BX WDM)	32	8
光纖埠 (100BASE-SFP)	16	4
光纖埠 (1000BASE-SX/LX/BX)	32	8
光纖埠 (1000BASE-SFP)	16	4
PoE 網路埠	-	-
網頁管理	-	-
告警介面	-	-
效 能		
Auto-negotiation,MDI/MDI-X 自動協調	√	√
流量控制	√	√
儲存與轉發	√	√
Link Fault Pass Through	√	√
機 構		
機殼	金屬	金屬
安裝方式 *	R	D
安裝尺寸 (mm) (寬 x 深 x 高)	440 x 276 x 90	130 x 164 x 92
電 源		
電源輸入數	2	2
100 - 240VAC	√	-
Terminal Block	±48VDC	12VDC
DC Jack	-	-
AC to DC Adapter	-	-
環 境		
0 to 45°C (32 to 113°F)	√	√
-10 to 60°C (14 to 140°F)	-	-
法規標準		
CE / FCC / VCCI	√	√
ISA 12.12.01 / UL 1604	-	-
EN 50121-4	-	-
UL 508	-	-
UL/cUL 60950-1	√	√

* C: 收容機箱 D: 導軌式安裝, P: 平面式安裝, R: 機架式安裝, W: 壁掛式安裝

選擇我們，成為您致勝關鍵的合作夥伴

益網科技 - When connectivity is crucial

我們明白品質對您來說很重要。做為強固級網絡解決方案的領導者，我們密切監控每一步設計過程，從組件選擇、全面的設計驗證，以及生產前的測試；益網科技在製造的每個階段對流程進行嚴格的管理，以確保交付予您是最高質量的產品。

我們的強固級產品需要通過長達 72 小時溫度測試，這當中需要將工作溫度設定在 -40 到 85°C (-40 到 185°F) 並反覆進行數據傳輸。此外，各項產品也必需符合嚴格的工業級品檢，如衝擊、振動、落下、靜電放電、電脈衝抗擾度、浪湧抗擾度和 EMI 輻射。所有測試均在益網科技的實驗室中進行，以確保我們的產品滿足或超過我們所服務市場的嚴苛要求。

此外，益網擁有 ISO 認證的作業流程及製造基地，符合歐盟 RoHS 環保規範，並積極配合綠色政策之執行。我們承諾，將全面降低環境衝擊與負荷，以落實綠色供應鏈的願景。

對客戶負責、對環境負責，是益網品牌的使命。對於連接至關重要的任務關鍵型應用程序，益網科技將是提供您最佳解決方案的好夥伴。



益網科技股份有限公司

全球營運（總部）

231 新北市新店區寶橋路235巷6弄2號8樓

電話：+886-2-6629-8986

傳真：+886-2-6629-6577

Email: info@etherwan.com.tw

美國銷售中心

2301 E. Winston Road, Anaheim, CA 92806

電話：+1-714-779-3800

傳真：+1-714-779-3806

Email: info@etherwan.com

www.etherwan.com



EtherWAN Systems, Inc. All rights reserved.

W69G-EW25021AC

益網科技致力於不斷精進產品，本司保留一切權利，可於任何時間及不時更改、增加、減少及／或修改型錄內容，並無需作出通知。