


# EX19164A

Unmanaged 16-Port Gigabit PoE Ethernet Switch



## Product Highlights

### Power over Ethernet

- Total PoE power budget of 250W to deliver sufficient power to all connected PoE devices
- Overloading protection
- Power and data over a single cable with gigabit speed capable of handling cameras with 4K resolution and higher and other high bandwidth devices

## Overview

EtherWAN's EX19164A is a 16-port Gigabit Power over Ethernet switch with high performance and features suited for small-business and commercial environments. The EX19164A is equipped with 16 10/100/1000BASE-T(X) PoE+ ports with 4 being combo ports with 1000BASE SFP for fiber. With full wire speed throughput, port speeds up to gigabit for 4K cameras and higher, and a power budget of 250W, the EX19164 is the perfect solution for security networks.

## Ordering Information

### Model

|                 |  |
|-----------------|--|
| <b>EX19164A</b> | 16-port 10/100/1000BASE-T(X) PoE (4-port 1000 SFP combo) |
|-----------------|--|

\* Rack mounting kit included.

# Hardware Specifications

|                            |  |   |
|----------------------------|--|---|
| <b>Interface</b>           |  | + |
| Ethernet                   | 10/100/1000BASE-T(X): 16 ports<br>1000BASE SFP: 4 ports (combo with ports 13-16)   |   |
| LED Indicators             | Per Unit: Power<br>Per Port PoE: Status<br>Per Port Link: Link/Activity  |   |
| Reset Button               | Restore factory default settings   |   |
| <b>Technology</b>          |  | + |
| Standards                  | IEEE 802.3 10BASE-T<br>IEEE 802.3u 100BASE-TX<br>IEEE 802.3ab 1000BASE-T<br>IEEE 802.3z 1000BASE-SX/1000BASE-LX<br>IEEE 802.3x Full duplex and flow control<br>IEEE 802.3af Power over Ethernet (PoE)<br>IEEE 802.3at Power over Ethernet (PoE+) |   |
| Switching Fabric           | 32Gbps   |   |
| MAC Table Size             | 8K   |   |
| Packet Buffer Memory       | 4Mb  |   |
| Forward and Filtering Rate | 14,880pps for 10Mbps<br>148,880pps for 100Mbps<br>1,488,000pps for 1000Mbps  |   |
| Processing Type            | Store-and-Forward<br>Auto-Negotiation<br>Half-duplex back-pressure full-duplex flow control<br>Auto MDI/MDIX   |   |
| <b>Power</b>               |  | + |
| Input                      | 100-240VAC, 50/60Hz  |   |
| Power Consumption          | Device: 23W (without PoE)<br>PoE Power Budget: 250W  |   |
| <b>Physical</b>            |  | + |
| Casing Material            | Metal  |   |
| Dimensions                 | 440 x 220 x 44mm (W x D x H)<br>17.3" x 8.66" x 1.73"  |   |
| Weight                     | 6.6lbs (3kg)   |   |
| Installation Type          | Rack mounting  |   |
| <b>Environmental</b>       |  | + |
| Operating Temp.            | 0 to 50°C (32 to 122°F)  |   |
| Storage Temp.              | -20 to 80°C (-4 to 176°F)  |   |
| Relative Humidity          | 10% to 90% (non-condensing)  |   |
| <b>Regulatory</b>          |  | + |
| ISO                        | Manufactured in ISO-9001 facility  |   |
| EMI                        | FCC Part 15 Class A  |   |
| Safety                     | UL 60950-1   |   |

|                        |  |   |
|------------------------|--|---|
| <b>Warranty</b>        |  | + |
| Length                 | 3 Years  |   |
| Details                | <a href="http://www.etherwan.com/support/warranty-policy">www.etherwan.com/support/warranty-policy</a> |   |
| <b>What's Included</b> |  | + |
| Device                 | Ethernet Switch  |   |
| Power                  | AC power cord  |   |
| Installation           | Mounting brackets, screws  |   |
| Documentation          | Quick Install Guide  |   |

# Dimensions

