


AiR PACE CX 系列

工業級智慧型 IoT 物聯網邊緣計算閘道器 (採專案最少數量限制)



產品亮點

Highly-reliable network connection

- » Offers multiple Internet access methods: Gigabit Ethernet, Global 3G/LTE Cat. 4 networks
- » With support of Dual-SIM, redundant link backup, and VRRP hot standby, the gateway ensures continuous connection by seamless transition to a backup link when main link fails

Powerful edge computing capabilities

- » ARM Cortex-A53 processor, 1GHz main frequency, up to 1GB DDR3 RAM and 8GB eMMC FLASH give the gateway powerful Edge computing capabilities to perform data optimization, real-time response, agile connection, smart applications, security and privacy protection at the IoT Edge

Compatible with multiple industrial protocols

- » Modbus RTU, Modbus TCP
- » MQTT

產品介紹

AiR PACE, the EtherWAN Industrial Smart IoT Edge Computing Gateway for Internet of Things (IoT), is a configurable and manageable wireless gateway. The AiR PACE features various interfaces and supports useful user application tools to meet IoT applications. It provides real-time data analysis and intelligent processing at the fieldbus edge, which is more effective and secure. The AiR PACE is both Microsoft Azure IoT edge certified and AWS IoT Greengrass qualified. Quick-to-deploy, the AiR PACE smart gateway can be tailored to any IoT application needs.

EtherWAN — "When Connectivity is Crucial."

頻率段

+ Cellular (*AiR PACE 1-XX-CX Series)

Sku Code	4G LTE		3G	2G	Region
	FDD LTE	TDD LTE	WCDMA	GSM/EDGE	
TA	B1(2100)/ 3(1800)/ 4(AWS)/ 5(850)/ 7(2600)/ 8(900)/ 28(700 APT)	B40(2300)	B1(2100)/ 2(1900)/ 5(850)/ 8(900)	B2(1900)/ 3(1800)/ 5(850)/ 8(900)	Taiwan & Australia
EA	B1(2100)/ 3(1800)/ 7(2600)/ 8(900)/ 20(800) /B28A (700)	B38(TD 2600)/ 40(TDV 2300)/ 41(TD 2500)	B1(2100)/ 8(900)	B3(1800)/ 8(900)	EU & APAC

產品特色

+ Functions

Cellular

3GPP, 3G/4G, IP Pass-through, IPv4
Band management for band lock

Ether-WAN

Dynamic IP, Static IP, PPPoE, PPTP, L2TP

Protocols

DHCP Server/Relay
Port-based, Tag-based VLAN
QoS
LLDP

Port Forwarding

NAT 1-1, 1-Many, transversal, Virtual
Server/Computer, DMZ, VPN Pass-through

+ Network Management

Configuration

Web Console, CLI, Command Script, Python

Management

SNMP v1/v2c/v3, AiR PACE MIB

System

Upgrade, Backup & Restore, Reboot & Reset,
SysLog

Diagnostic

Ping, Traceroute, Packet Analyzer, Sniffer (Field
communicating data logging), Diagnostic tool

+ Security

VPN

IPSec (Up to 16 Tunnels), OpenVPN, PPTP, L2TP, GRE

Firewall

SPI Firewall with Stealth Mode, IPS

Access Control

URL Blocking, URL Blocking, MAC Filter

+ Field Communication**Virtual COM**

RFC2217, TCP Client, TCP Server, UDP

Modbus

Gateway for Modbus TCP, Modbus RTU/ASCII

Master/Slave Access

Slave for Device Status/Information Access

Data Interchange

MQTT Broker, MQTT Client

Data Logging

Sniffer, Off-line/Full-time Proxy, Mixed modes

+ Service**Cellular Toolkit**

Data Usage, SMS, SIM PIN, USSD, Network Scan

Event Handling

User Defined Manage/Notify Event; Action &

Trigger by SMS, Mail, Syslog, SNMP Trap,

Modbus, I/O

Development Platform

Python Customization Development

Amazon AWS Greengrass

Microsoft Azure IoT Edge

User Application Tool

Node-RED

產品規格

+ Platform

CPU: ARM Cortex A53 1.35GHz Dual Core
DRAM: 1GB DDR3 Memory
Storage Pre-installed: 8GB eMMC
Storage Slot: MicroSD Slot x 1 for SD 3.0 (SDXC)
Compliant Storage Expansion

+ Cellular

Standards

4G LTE: FDD-LTE, TDD-LTE, Transfer rate (max):
LTE FDD: 150Mbps down; 50Mbps up; LTE TDD:
130Mbps down; 35Mbps up
3G: WCDMA, Transfer rate (max): 42Mbps
down; 5.76Mbps up
2G: GSM/EDGE, Edge Transfer rate (max):
236.8Kbps down & up

SIM Slot

2 x microSIM card slots

+ Ethernet

Standards

IEEE 802.3 10/100/1000BASE-T
IEEE 802.3u 100BASE-T(X)
IEEE 802.3ab 1000BASE-T(X)
IEEE 802.1x Flow control
Full/Half duplex mode
Auto MDI/MDI-X connection
Auto negotiation speed

Ports

1 x RJ-45 GbE (WAN/LAN Configurable) +2 x RJ-

45 GbE

+ Serial

Ports

1 x RS-232/RS485 (4-pin Terminal Block)

Signal

RS-232: TxD, RxD, GND

RS-485: D-/A, D+/B, GND

+ I/O

Analog Input

2 x AI

Conversion: 12bit ADC

Input Range: 0-10V

Resolution: 2.5mV

Digital Input

2 x DI (Isolated, "Logic 0": 0-2V, "Logic 1": 5-30V)

Digital Output

2 x DO (Isolated, Non-Relayed Output,
24V/300mA for each port)

Connector

10-pin Terminal Block

+ USB

Standards

USB 2.0 Host

Ports

1 x USB Type A

+ Antennas

Cellular

2 x SMA Female (Main & Aux.)

+ LED Indicators

System

PWR x 1; Status x 1

Data

LAN1, LAN2, LAN3/WAN, 4G1L, Serial, LoRa*
(*LoRa Model Only)

Cellular Signal

4G1S

+ Power

Input

9-36VDC

AiR PACE 1-XX-CX: 14.5Watts (Max.), 8.5Watts
(Typical)

AiR PACE 1-XX-CL: 17Watts (Max.), 11Watts
(Typical)

+ Physical

Casing Material

Metal Case

IP Rating

IP30

Dimension

40 x 117.8 x 161.3mm (W x D x H)

40 x 127.4 x 161.3mm with DIN-Rail kit (W x D x H)

Weight

0.76kg (1.67lbs)

Installation Type

DIN-Rail mounting

Wall mounting Bracket* (*Optional)

+ Environment Limits

Operating Temp.

-30 to 70°C (-22 to 158°F)

Storage Temp.

-40 to 85°C (-40 to 185°F)

Relative Humidity

5% to 95% (non-condensing)

+ Regulatory Approvals

Safety

EN 60950-1


EN 62368-1: 2014

Emissions/Immunity

CE/NCC BSMI


產品外觀圖

Image not found or type unknown



產品尺寸圖

Image not found or type unknown



訂購型號

+ 4G LTE Gateway

Model	Description	RF	Region
AiR PACE 1-TA-CX	Industrial Smart IoT Edge Computing Gateway	Cellular LTE Cat. 4	Taiwan & Australia
AiR PACE 1-EA-CX	Industrial Smart IoT Edge Computing Gateway	Cellular LTE Cat. 4	EU & APAC



© EtherWAN Systems, Inc. All rights reserved. 20250206

EtherWAN is constantly developing and improving products. Specifications are subject to change without notice and without incurring any obligation.