

EN400 系列

PCI-Express 100BASE-FX/SFP 乙太網路介面卡



產品亮點

本產品自2021年07月31日起停產。請點選 [此處](#) 尋找替代產品。

- » SFP slot and low-profile version availability
- » Supports PCI Express 1.1
- » Wake-on-LAN and remote wake-up support
- » Supports 1-Lane 2.5Gbps PCI Express Bus
- » 0 to 50°C operating temperature range

產品特色

- Compliant IEEE802.3 10BASE-T, 802.3u 100BASE-TX/FX/SFP
- Supports PCI Express 1.1
- Various Type of Cable Support - Twisted Pair Cable or Fiber Optic Cable
- Plug-and-Play Support
- Wake-on-LAN and remote wake-up support
- Full Duplex flow control (IEEE 802.3x)
- IEEE 802.1P Layer 2 Priority Encoding
- IEEE 802.1Q VLAN tagging
- Supports power down/link down power saving (for EN400TX)
- Supports 1-Lane 2.5Gbps PCI Express Bus
- 0 to 50°C operating temperature range

產品規格

Technology

Standards

- IEEE802.3
- IEEE802.3u

Protocols

- IEEE802.3x Full-duplex flow control Driver
 - Microsoft Windows 98, Windows ME, Windows XP, Windows 2000, Windows 2003, Windows Vista, Windows 7 and Windows 2008
 - SCO Unix 5.0.6 and 5.0.7
 - SCO OpenServer 6 and UnixWare 7.1.x.
 - FreeBSD 7.x and 8.0
 - Linux kernel 2.6.x and 2.4.x (Support x86 and x64)
 - Novell server driver (Support OS 6.x, 5.x), client for DOS (ODI driver)
 - MacOS 10.4 and 10.5 on Intel-based Mac computer, 10.6 on Intel-based Mac computer.
-

Power

Power Consumption

- 2W Max.
-

Mechanical

Dimensions:

* Low Profile

- 80mm (W) x 119.2mm (D)
(3.2"(W) x 4.76"(D))

* Regular

- 117.5 mm (W) x 119.2 mm (D)
(4.7"(W) x 4.76"(D))

Weight

- 80g (0.18lb.)
-

Interface

Ethernet Port

- 100BASE-FX: 1 port

LED Indicators

- Per Unit: Link/Activity, SPD
-

Environment

Operating Temperature

- 0°C to 50°C (32°F to 122°F)

Storage Temperature

- -10°C to 70°C (14°F to 158°F)

Ambient Relative Humidity

- 5% to 95% (non-condensing)
-

Regulatory Approvals


ISO

- Manufactured in an ISO9001 facility

EMI

- CE Mark Class B
 - FCC Part 15 Class B
 - VCCI Class B
-

產品尺寸圖



訂購型號

Model

EN400C	100BASE-FX Multi Mode (SC) Ethernet Adapter
EN400T	100BASE-FX Multi Mode (ST) Ethernet Adapter
EN400C-20	100BASE-FX Single Mode (SC) -20Km Ethernet Adapter
EN400C-40	100BASE-FX Single Mode (SC) -40Km Ethernet Adapter
EN400T-20	100BASE-FX Single Mode (ST) -20Km Ethernet Adapter
EN400CA-20	100BASE-FX Single Mode (SC) WDM-TX :1310nm/RX :1550nm -20Km Ethernet Adapter
EN400CB-20	100BASE-FX Single Mode (SC) WDM-TX :1550nm/RX :1310nm -20Km Ethernet Adapter
EN400CA-40	100BASE-FX Single Mode (SC) WDM-TX :1310nm/RX :1550nm -40Km Ethernet Adapter
EN400CB-40	100BASE-FX Single Mode (SC) WDM-TX :1550nm/RX :1310nm -40Km Ethernet Adapter
EN400LC	100BASE-FX Multi Mode (LC) -2Km Ethernet Adapter
EN400PB	100BASE-SX (SC) 850nm Multi-Mode Fiber Fast Ethernet Adapter
EN400SFP	100BASE SFP Ethernet Adapter
EN400PC	100BASE-FX Multi Mode (SC) Ethernet Adapter (Low profile)
EN400PC-10	100BASE-SX (SC) 1310nm Single-Mode Fiber Fast Ethernet Adapter (10km)
EN400PT	100BASE-FX Multi Mode (ST) Ethernet Adapter (Low profile)
EN400PC-20	100BASE-FX Single Mode (SC) -20Km Ethernet Adapter (Low profile)
EN400PC-40	100BASE-FX Single Mode (SC) -40Km Ethernet Adapter (Low profile)
EN400PT-20	100BASE-FX Single Mode (ST) -20Km Ethernet Adapter (Low profile)
EN400PCA-20	100BASE-FX Single Mode (SC) WDM-TX :1310nm/RX :1550nm -20Km Ethernet Adapter (Low profile)
EN400PCB-20	100BASE-FX Single Mode (SC) WDM-TX :1550nm/RX :1310nm -20Km Ethernet Adapter (Low profile)
EN400PCA-40	100BASE-FX Single Mode (SC) WDM-TX :1310nm/RX :1550nm -40Km Ethernet Adapter (Low profile)
EN400PCB-40	100BASE-FX Single Mode (SC) WDM-TX :1550nm/RX :1310nm -40Km Ethernet Adapter (Low profile)
EN400PLC	100BASE-FX Multi Mode (LC) -2Km Ethernet Adapter (Low profile)
EN400PSFP	100BASE SFP Ethernet Adapter (Low profile)



© EtherWAN Systems, Inc. All rights reserved. 20220721

EtherWAN is constantly developing and improving products. Specifications are subject to change without notice and without incurring any obligation.