EG97244 系列

強固級網管型 8 埠10/100/1000BASE-T +16 埠 100/1000BASE SFP+ 4 埠 1G/2.5G/10G SFP + 第 3 層乙太網路交換器



產品介紹

什麼是第三層交換器 (Layer 3 Switch) ?

EtherWAN 的 EG97244 產品為高效能超高速第 3 層乙太網路交換器。 EG97244 具有用於光纖的多個千兆位 (1G SFP) 連接埠以及 4 個 10 千兆 (10G SFP+) 的連接埠，主要定位是應用於骨幹型網路上。產品本身具有高度彈性、快速和穩定可靠的優勢，可廣泛應用於城市基礎設施、交通、安全和以及其它與網路串聯相關的網路管理工程領域中。

EtherWAN — "When Connectivity is Crucial."

產品亮點

具高頻寬且多點網路連結的靈活性與傳輸能力

16 個 100/1000M 雙速率 SFP 連接埠 ，用於多組光纖連接

4 個 1G/2.5G/10G 雙速率 SFP+ 連接埠，用於連接到核心與集線核心層

8 個 10/100/1000BASE-T RJ45 連接埠，用於乙太網路的銅線連接

適用於不通風和惡劣環境的強固設計

-40 至 75°C（-40 至 167°F）寬工作溫度範圍

無風扇設計

高耐溫衝擊和高雜訊抗噪

完備的第 3 層網路功能等級

硬件等級的路由優化

故障隔離的再加強

運用第 3 層網路功能將整個網絡連接在一起

專案合規等級的網路產品

符合美國政府 TAA 專案標準

符合 NEMA TS2 等級

符合 UL 安全認證

穩定且安全的網路管理機制

連接埠端口控管 (Port control)

透過風暴 (Storm detection and control) 偵測和控管

可搭配 eVue™ 和 eLite 軟體來做網路監管

終身保固服務

提供免費技術支援

提供免費韌體升級服務

包含 ECN 和 EOL 通知

產品特色

Interface

CLI, Telnet, Web GUI

Management

Firmware upgrade
Configuration backup
DHCP Server/Client
RMON (Remote Monitoring)
Port Mirroring
NTP (Network Time Protocol) synchronization
LLDP (Link Layer Discovery Protocol)
IPv4/IPv6
SNMP v1/v2c/v3

Security

MAC Address filtering
Enable/Disable port
Storm control
System logging
Remote authentication through RADIUS and TACACS+
Complex password support
Multi-user login and privileged access management
SSH for CLI and Telnet security
SSL and HTTPS for web security
ACL (Access Control List, up to 4096 entries)
TLS 1.3

Layer 3 Features IPv4

Unicast Routing

Static Routing (1K)
RIP v1/v2
OSPF v2

Multicast Routing

PIM-DM
PIM-SM
PIM-SSM

Routing Redundancy

VRRP

Layer 3 Features IPv6

IPv6 Unicast Routing

RIPng
OSPF v3

IPv6 Multicast Routing

PIM6-DM
PIM6-SM

IPv6 Routing Redundancy

VRRP v3

Quality of Service (QoS)

Priority Queues: 8 queues per port

Traffic classification based on IEEE 802.1p CoS (Cost of Service), DSCP (Differentiated Services Code Point), WRR (Weighted Round Robin), and strict mode

Rate Limiting (Ingress/Egress)

Layer 2 Features

Auto-negotiation for port speed and duplex

Flow Control

IEEE 802.3x full duplex mode

Back-pressure half duplex mode

Redundant Protocols

IEEE 802.1D STP

IEEE 802.1w RSTP

IEEE 802.1s MSTP

ITU-T G.8032 Ethernet Ring Protection Switch (ERPS)

VLANs

IEEE 802.1Q Tag VLANs

GVRP

GMRP

Private VLANs and MAC/Subnet/Protocol Based VLANs

Link Aggregation

Static Trunk

IEEE 802.3ad LACP

IGMP Snooping v1/v2/v3

Software Properties and Performance

Switch IC Capability

320Gbps

Forwarding Rate

238.08Mpps

Total VLAN Entries

256 (4096 VID)

Jumbo Frame Size

12KB

MAC Table Size

24K

Packet Buffer Memory

32M bits

L2 Routes

Up to 24,000 unicast and 1,000 multicast routes

L3 IPv4 Routes

Up to 8,000 unicast and 8,000 multicast routes

L3 IPv6 routes

Up to 2,000 unicast routes

產品規格

Interface

Ethernet

8 x 10/100/1000BASE-T

16 x 100/1000BASE SFP

4 x 1G/2.5G/10G SFP+

Console

1 x RJ45

Config Backup

1 x USB (Type A Connector)

Alarm Contact

Relay output, current capacity 0.6A/30VDC

LED Indicators

Per Unit: Power 1, Power 2, Alarm

Per Port: Link/Activity

Power

Input

VTR: ±48VDC Redundant (Terminal block)

VWR: 100-240VAC Redundant (Terminal block)

VCR: 100-240VAC Redundant (AC Inlet)

Power Consumption

75W Max

Environmental

Operating Temp.

-40 to 75°C (-40 to 167°F)

Storage Temp.

-45 to 85°C (-49 to 185°F)

Relative Humidity

5% to 95% (non-condensing)

MTBF

1,143,890 hours

What's Included

Device

Ethernet Switch

Cables

1 Console Cable

Power

1 AC Power Cord

Installation

Mounting brackets, screws

Documentation

Quick install guide

Technology

Standards

IEEE 802.3 10BASE-T

IEEE 802.3u 100BASE-TX/100BASE-FX

IEEE 802.3ab 1000BASE-T

IEEE 802.3ad link aggregation control

IEEE 802.3z 1000BASE-SX/1000BASE-LX

IEEE 802.3x full duplex and flow control

IEEE 802.1D STP

IEEE 802.1p QoS

IEEE 802.1Q Tag VLANs

IEEE 802.1s MSTP

IEEE 802.1w RSTP

IEEE 802.1x PNAC

IEEE 802.1ab LLDP

IEEE 802.3 bz for 2.5Gbps support

Forward/Filtering Rate

14,880pps for 10Mbps

148,810pps for 100Mbps

1,488,100pps for 1000Mbps

3,720,000pps for 2.5Gbps

14,881,000pps for 10Gbps

Processing Type

Store-and-forward

Auto-negotiation

Half-duplex back-pressure and full-duplex flow control

Auto MDI/MDIX

System Memory

4Gb DDR3 SDRAM

Flash Storage

2GB

Regulatory

ISO

Manufactured in ISO-9001 facility

EMC

EN 55032

EMI

FCC Part 15B Class A

VCCI Class A

EN 61000-6-4

EMS

EN 61000-4-2 (ESD)

EN 61000-4-3 (Radiated RFI)

EN 61000-4-4 (Burst)

EN 61000-4-5 (Surge)

EN 61000-4-6 (Induced RFI)

EN 61000-4-8 (Magnetic field)

Safety

UL 62368

Traffic

NEMA TS2

Rail

EN 50121-4

Vibration

IEC 60068-2-6

Shock

IEC 60068-2-27

Free Fall

FED STD 101C Method 5007.1

Physical

Casing Material

Aluminum

Dimensions

442 x 325 x 44mm (W x D x H)
17.4" x 12.8" x 1.73"

Weight

5.6kg (12.3lbs)

Installation Type

Rack mounting

IP Rating

IP30

Warranty


Length

Limited Lifetime


Details

www.etherwan.com/support/warranty-policy

產品尺寸圖





產品應用圖


L3 10G Fiber
L2 1G Fiber or 10/100/1000M Copper
Traffic Management Center (TMC)
EG97023
EG97023
Core
EG97244
EG97244
EG97244
EG97244
Distribution
Cameras
Traffic Control
Traffic Billboards
Sub Area Network
Edge

管理軟體

Network Management	eVue™ Network Configuration and Monitoring Tool
Network Discovery	eLite™ Network Discovery and IP Configuration Tool





訂購型號

Model



	EG97244-4VZ
10/100/1000BASE T(X)	8
1/2.5/10G SFP+	16
1G/10G SFP+	4
	訂購諮詢

Power Input Interface (Z)

TR	±48VDC Redundant (Terminal Block)
WR	100-240VAC Redundant (Terminal Block)
CR	100-240VAC Redundant (AC Inlet)

Accessories

Hardened 100BASE SFP Modules	www.etherwan.com/products/sfp-fiber-transceiver
Hardened Gigabit SFP Modules	www.etherwan.com/products/sfp-fiber-transceiver
Power Supplies	www.etherwan.com/products/power-supplies/power-adapters
EX41-2750A240	Power Module for EG97244 series, 100-240VAC PSU (75W), AC Inlet

© EtherWAN Systems, Inc. All rights reserved. 20261027
EtherWAN is constantly developing and improving products. Specifications are subject to change without notice and without incurring any obligation.