EX71000 系列

強固級網管型 8埠10/100BASE +2埠Gigabit 乙太網路交換器(SFP選擇組合)



產品介紹

本產品自2026年8月6日起停產。 請點選此處 尋找替代產品

EX71000強固級乙太網路交換器，配備8個10/100base連接埠及2個Gigabit光纖埠，可彈性搭配多種介面組合：SX/LX/BX/WDM及SFP插槽。支援標準備援通訊協定STP/RSTP/MSTP，透過益網獨家技術Alpha-Ring環狀網路備援機制，可在網路發生斷線時迅速啟動備援機制，於15毫秒內快速恢復連線通訊。

EX71000系列擁有完整的管理功能，支援IPV4/IPV6 協定, port security, IGMP snooping, VLANs, GARP 協定, 和LACP；可透過網頁瀏覽、Telnet,、SNMP、RMON、TFTP和 RS-232 console 管理介面。工業級設計，可在-40 到 75°C 寬溫環境下穩定運作，是嚴苛關鍵網路應用架構的最佳選擇。

EtherWAN — "When Connectivity is Crucial."

產品亮點

Hardened-Grade for Non-Ventilated & Harsh Environments

Wide operating temperature range -40 to 75°C (-40 to 167°F)

Fanless operation

High impact, thermal shock, and electrical noise resistance

Compliance

EN 50121-4 certified for railway applications

NEMA TS2 rated

UL certified for safety

Management/Security Features

Port control

802.1x port-based network access control and remote authentication through RADIUS

Configure and monitor with eVue™ and eLite™

Support

Complimentary Technical Support

Free Firmware Upgrades

Limited Lifetime Warranty

產品特色

Interface

CLI, Telnet, Web GUI

SNMP v1/v2c/v3

Management

Firmware upgrade

Configuration backup via TFTP

DHCP Server/Client

RMON (Remote Monitoring): group 1, 2, 3, 9

Port Mirroring: TX/RX and both

NTP (Network Time Protocol) synchronization

IEEE 802.1ab LLDP (Link Layer Discovery Protocol)

IPv4/IPv6

Security

MAC Address Filtering

Enable/Disable port

Storm control (Broadcast and multicast types)

IEEE 802.1x LAN Access control

Remote authentication through RADIUS and TACACS+

SSH for CLI and Telnet security

SSL for web security

System log (Remote/Local)

Multi-level user account/password against unauthorized configuration

Quality of Service (QoS)

Priority Queues: 4 queues per port

Traffic classification based on IEEE 802.1p CoS, DSCP, WRR and strict mode

Rate Limiting (Ingress/Egress)

Layer 2 Features

Auto-negotiation for port speed and duplex

Flow Control

IEEE 802.3x full duplex mode

Back-Pressure half duplex mode

Redundant Protocols

IEEE 802.1D STP

IEEE 802.1w RSTP

IEEE 802.1s MSTP

EtherWAN's Alpha-Ring network fault recovery (<15ms)

VLANs

Port-based VLANs

IEEE 802.1Q Tag VLANs (128 groups, 4096 VID)

GVRP

GMRP

Link Aggregation

Static Trunk (2 groups, support MAC base)

IEEE 802.3ad LACP

IGMP Snooping v1/v2/v3

產品規格

Interface

Ethernet

4, 6 or 8 x 10/100BASE-T(X)

0 or 4 x 100BASE-FX

0, 1 or 2 x Gigabit

Console

1 x DB9 RS-232

Alarm Contact

1 x Relay output, current capacity 0.6A/30VDC

LED Indicators

Per Unit: Power 1, Power 2, Alarm

Per Port: Link/Activity, Speed

Environmental

Operating Temp.

-40 to 75°C (-40 to 167°F)

Tested @ -40 to 85°C (-40 to 185°F)

Storage Temp.

-45 to 85°C (-49 to 185°F)

Relative Humidity

5% to 95% (non-condensing)

Technology

Standards

IEEE 802.3 10BASE-T

IEEE 802.3u 100BASE-TX/100BASE-FX

IEEE 802.3ab 1000BASE-T

IEEE 802.3z 1000BASE-SX/1000BASE-LX

IEEE 802.3x Full duplex and flow control

IEEE 802.1p QoS

IEEE 802.1Q Tag VLANs

IEEE 802.1w RSTP

IEEE 802.1x PNAC

Forward/Filtering Rate

14,880pps for 10Mbps

148,810pps for 100Mbps

1,488,100pps for 1000Mbps

Packet Buffer Memory

12M bits

Processing Type

Store-and-Forward

Auto-negotiation

Half-duplex back-pressure and IEEE 802.3x Full-duplex flow control

Auto MDI/MDIX

Address Table Size

16K MAC Addresses

Regulatory

ISO

Manufactured in ISO-9001 facility

EMI

FCC Part 15B Class A

EN 55032

EN 61000-6-4

EN 61000-3-2

EN 61000-3-3

EMS

EN 61000-6-2

EN 61000-4-2 (ESD)

EN 61000-4-3 (Radiated RFI)

EN 61000-4-4 (Burst)

EN 61000-4-5 (Surge)

EN 61000-4-6 (Induced RFI)

EN 61000-4-8 (Magnetic Field)

Safety

UL 61010

ISA 12.12.01

Vibration

IEC 60068-2-6 Fc

Shock

IEC 60068-2-27 Ea

Free Fall

FED STD 101C Method 5007.1

Industrial Compliance

NEMA TS2

EN 50121-4

Power

Input

12-48VDC Redundant (Terminal block)

Power Consumption

7.5W Max. 0.31A@24VDC

Protection

Reverse Polarity Protection

Physical

Casing Material

Aluminum

IP Rating

IP30

Dimensions

60 x 125 x 145mm (W x D x H)
2.36" x 4.92" x 5.7"

Weight

1.05kg

Installation Type

DIN-rail mounting

Warranty

Length

Limited Lifetime

Details

www.etherwan.com/support/warranty-policy

What's Included

Device

Ethernet Switch


Cables

1 Console Cable


Documentation

Quick Install Guide

產品尺寸圖



Top
60mm (2.36")
125mm (4.92")
145mm (5.7")
Front
Side
Back
Bottom


產品應用圖


Exhaust Control System
Fire Detection System
IP Camera System
Speed Display
Exhaust Control System
PLC
PLC
EX71000
Emergency Phone
EX71000
Alpha-Ring < 15ms
EX71000
EX71000
Fiber-optic
Cat.5 Ethernet
Serial-Cable
The EX71000 utilized in an intelligent tunnel solution

管理軟體

Network Management	eVue™ Network Configuration and Monitoring Tool
Network Discovery	eLite™ Network Discovery and IP Configuration Tool





訂購型號

Model

EX71802-0YB	8-port 10/100BASE-TX + 2-port Gigabit
EX71620-X0B	6-port 10/100BASE-TX + 2-port 100BASE-FX
EX71622-XYB	6-port 10/100BASE-TX + 2-port 100BASE-FX +2-port Gigabit
EX71440-X0B	4-port 10/100BASE-TX + 4-port 100BASE-FX

* DIN-Rail mounting kit included.

100FX Fiber Options (X)

1	Multi Mode (SC) - 2Km
2	Multi Mode (ST) - 2Km
A	Single Mode (SC) - 20Km
B	Single Mode (SC) - 40Km
V	100BASE SFP (DDM)

* More 100FX Fiber options also available upon request.

Gigabit Port Options (Y)

1	10/100/1000BASE-TX
3	1000BASE-SX (SC) - 550m
4	1000BASE-SX (SC) - 2Km
5	1000BASE-SX (ST) - 550m
A	1000BASE-LX (SC) - 10Km
B	1000BASE-LX (SC) - 20Km
R	1000BASE-BX (SC) WDM-TX: 1310nm/RX: 1550nm-20Km
S	1000BASE-BX (SC) WDM-TX: 1550nm/RX: 1310nm-20Km
V	100/1000BASE SFP (DDM)

* More Gigabit options also available upon request.

Accessories

Hardened SFP Modules	www.etherwan.com/products/sfp-fiber-transceiver

DIN-Rail Power Supplies	www.etherwan.com/products/din-rail-power-supply (*)
***Recommended Power Supply**	HDR-30-24 30W 24VDC DIN-Rail Power Supply
EB-232	Configuration Backup and Restoration Tool

© EtherWAN Systems, Inc. All rights reserved. 20260313
EtherWAN is constantly developing and improving products. Specifications are subject to change without notice and without incurring any obligation.